

M. P. MÖLLER Organ Factory

Pipe Organ No. M-4152 **Date** February 26, 1986
For FIRST CHURCH OF CHRIST, SCIENTIST, DAYTONA BEACH, FLORIDA
Action Electro-Pneumatic **Console** Present - Detached
Casing No. None **Finish** Present - no change
Decorations None **Motor** Present 1/2 HP, Style 2-P-2116
Width of Key-bed Standard **Stop Controls** Tilting Tablets
No. Manuals TWO AND PEDAL **Wind Pressure** 3-1/2"
To be Completed June 1, 1986 **Blower Pipe furnished by** Purchaser

SPECIFICATIONS

REPAIRING FIRE DAMAGED ORGAN
 OPUS 11521 - 1981 27859

CONSOLE Clean and polish cabinet, bench and pedal keyboard.
 Clean all solenoids.
 Replace cracked keys.
 Recover expression pedal.

MAIN AND OFFSET CHESTS Clean, releather, repaint and rewire Great chests.
 Install new magnet armatures and plugs in Great chests.
 Replace all Swell chests.

CHIMES Install new chimes and action.

EXPRESSION Paint and refelt Great shades reusing present motor.
 Replace Swell shades and install rebuilt motor.

RESERVOIRS Recover and refinish the following reservoirs and install new curtain valves as required:

- Two 2-0 x 2-0 manual
- One 1-6 x 2-0 offset
- One concussion
- One 2-0 x 2-0 blower

TREMOLOS Releather tremolos.

PIPES Replace the following pipes:

- 8 Gemshorn #1-32
- 4 Spitzprincipal #1-7
- 16 Contre Trompette #1-80

Repair remainder of pipes as follows:

Clean, round up and relacquer all metal pipes.
 Replace tuner slides thruout.
 Clean and repaint all wood pipes.

CABLES Install new cables and action current wires.

ACTION CURRENT Reuse present 10-15 volts, 30 amperes DC organ power unit.

BLOWER Repaint and reuse present 1/2 H.P., Style 2-P-2116 motor and blower.
Clean and repaint and refelt all wind conductors.

GENERAL Wash and clean all wood parts.

SPECIFICATIONS
FOR
CONSOLE AND ORGAN

GREAT ORGAN (Enclosed)

1	16	Bourdon.....present pipes and action.....	97 pipes
2	8	Principal.....present pipes and action.....	73 pipes
3	8	Gedeckt.....from #1.....	61 notes
4	8	Gemshorn.....from #13.....	61 notes
5	4	Octave.....from #2.....	61 notes
6	4	Gedeckt.....from #1.....	61 notes
7	2	Flute.....from #1.....	61 notes
8	II	Sesquialtera TC...present pipes and action.....	98 pipes
9	III-IV	Mixture.....present pipes and action.....	183 pipes
10		Chimes....new Mayland bells & actions, relay, transformer & volume control, A to F, #22 to 42.....	21 bells
11		Tremolo	

SWELL ORGAN (Enclosed)

12	8	Rohrflöte.....present pipes; new action.....	73 pipes
13	8	Gemshorn....new pipes #1-32, present pipes #33-80; new action.....	80 pipes
14	8	Gemshorn Celeste TC....present pipes; new action	49 pipes
15	4	Spitzprincipal....new pipes #1-7, present pipes #8-73; new action.....	73 pipes
16	4	Rohrflötefrom #12.....	61 notes
17	2	Spitzoctavefrom #15.....	61 notes
18	1-1/3	Larigot.....from #13..(repeat 12 top notes).....	61 notes
19	16	Contre Trompette...new pipes; new action.....	80 pipes
20	8	Trompette.....from #19.....	61 notes
21	4	Clairon.....from #19..(repeat 5 top notes).....	61 notes
22		Tremolo	

PEDAL ORGAN

23	32	Untersatz.....	from #1.....	32 notes
24	16	Bourdon.....	from #1.....	32 notes
25	8	Principal.....	from #2.....	32 notes
26	8	Gedeckt.....	from #1.....	32 notes
27	4	Octave	from #2.....	32 notes
28	4	Rohrflöte	from #12.....	32 notes
29	III	Mixture.....	from #9.....	32 notes
30	16	Contre Trompette.....	from #19.....	32 notes
31	8	Trompette.....	from #19.....	32 notes
32	4	Clairon.....	from #19.....	32 notes

COUPLERS

33 Swell to Great

ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3-4

Affecting Full Organ

PEDAL MOVEMENTS

Balanced Expression Pedal - Great Organ (8 contacts, reverse system)
 Balanced Expression Pedal - Swell Organ (8 contacts, reverse system)
 Balanced Crescendo Pedal with indicator light (green jewel)

ACCESSORIES

Motor and power unit on-off switch with indicator light
 Concave, radiating pedal clavier
 Organ bench with music shelf
 Music rack with light
 Pedal light

RVK/mr
 2/27/86