

M. P. MOLLER Organ Factory

Moser

Pipe Organ No.	R-753	Date	January 24, 1966
For	DUNCAN MEMORIAL METHODIST CHURCH, BERRYVILLE, VIRGINIA		
Action	Electro-Pneumatic	Console	Detached
Casing No.	No Change	Flitch	To customer's selection
Decorations	No Change	Motor	Present motor & blower. New DC organ power unit.
Width of Key-bed	Standard	Stop Controls	Tilting Tablets
No. Manuals	Two and Pedal	Wind Pressure	5"
To be Completed	March 31, 1966	Blower Pipe furnished by	Purchaser

SPECIFICATIONS

FOR

REBUILDING PRESENT MOLLER ORGAN OPUS 1828 - 1926
(Rebuilt R-276 - 1946)

- CONSOLE** Install new two manual electro-pneumatic detached tilting tablet type console, pedal keyboard and organ bench.
- MANUAL CHEST** Releather 341 manual pipe pouches.
Install 560 new stop action checks & eyelets.
Install 181 new duplex shifters.
Releather 8 stop action primaries and install new outside type magnets.
Releather two 73 note Primary Stations and install new outside type magnets.
- OFFSET CHESTS** Releather Great 8 Stopped Diapason unit action #1 to #85 incl.
Releather Swell 8 Vox Humana action #1 to #61 incl.
- CONTACT BOX** Releather two (2) present 73 note Contact Boxes and install new silver wire contact blocks.
- SWITCHES** Install the following new electro-pneumatic switches with stop actions:
- Great 8 Stopped Diapason - #1 to #73 incl. - 73 notes
 - Great 4 Flute - #13 to #85 incl. - 73 notes
 - Great Chimes - #1 to #21 incl. - 21 notes
 - Swell 8 Stopped Diapason - #1 to #73 incl. - 73 notes
 - Swell 4 Flute - #13 to #85 incl. - 73 notes
 - Swell 2-2/3 Flute Twelfth - #20 to #80 incl. - 61 notes
 - Swell 2 Piccolo - #25 to #85 incl. - 61 notes
 - Swell 8 Vox Humana - #1 to #61 incl. - 61 notes
- CHIMES** Releather and refelt 21 note chimes action.
Recover 21 chime pneumatics.
- PEDAL ORGAN** Releather 16 Bourdon action #1 to #32 incl. and install new outside type magnets.
Releather 16 Lieblich Gedeckt action #1 to #12 incl.

- EXPRESSION Recover 8 shade & bumper pneumatics.
Install 8 new shade jack assemblies and connecting wires.
- RESERVOIRS Recover the following reservoirs and install new curtain valves as required:
 - One (1) 3'-0" x 4'-0" Manual Reservoir
 - Two (2) 1'-6" x 2'-6" Pedal Reservoirs
 - One (1) Shade Reservoir
 - Two (2) Pneumatic Reservoirs
- TREMULO Install one new electro-pneumatic tremolo.
- PIPES Revoice the following pipes:
 - Swell 8 Oboe - 73 Pipes
 - Swell 8 Vox Humana - 61 Pipes
- CABLES Install new plastic covered cables as required.
- BLOWER Present motor & blower to be used without change.
Install new leather couplings.
Install new flexible rubber connections.
- ACTION CURRENT Install new 15 ampere DC organ power unit.
- GENERAL Entire organ with exception of blower and motor returned to factory of M. P. Moller, Inc. in Hagerstown, Maryland for rebuilding as specified above.

SPCIFICATIONS
For
CONSOLE AND ORGAN

- MANUAL COMPASS CC to Ch, 61 Notes
- PEDAL COMPASS CCC to G, 32 Notes
- WIND PRESSURE 5"
- PITCH A-440 @ 70° F

GREAT ORGAN

- 1 8 Open Diapasonpresent pipes; present action.....61 Pipes
- 2 8 Stopped Diapason (Unit).....present pipes; present action.....85 Pipes
- 3 8 Salicional.....present pipes; present action.....73 Pipes
- 4 8 Dulciana.....present pipes; present action.....73 Pipes
- 5 4 Flute.....from #2.....73 Notes
- 6 8 Oboe.....from #15.....73 Notes
- 7 Chimes.....present Deagan Class "E" tubes;
present action A to F #22 to #42 incl. 21 Tubes

18 notes
Sta.

