

M. P. MÖLLER Organ Factory

Pipe Organ No. 7024 Date June 5, 1941
 For PRESBYTERIAN CHURCH, SHIPPENSBURG, PENNSYLVANIA
 Action Electro-Pneumatic Console Detached
 Casing No. Present moved back Finish _____
 Decorations Present Motor Present
 Width of Key-bed _____ Stop Controls Stop-Keys
 No. Manuals 2 Wind Pressure No change
 To be Completed September 14, 1941 Blower Pipe furnished by Present

SPECIFICATIONS

2/22

GREAT ORGAN - Present Pipes and Chests

1	8'	Open Diapason.....	61	Pipes
2	8'	Dulciana.....	61	"
3	8'	Melodia.....	61	"
4	8'	Keraulophone.....	61	"
5	4'	Flute.....	61	"
6	4'	Octave.....	61	"
7	2'	Fifteenth.....	61	"
8	8'	Trumpet.....	61	"
9		Tremulant		

SWELL ORGAN - Present Pipes and Chests

1-61 New 62-73

10	16'	Bourdon.....	73	Pipes
11	8'	Open Diapason.....	73	"
12	8'	Stopped Diapason.....	73	"
13	8'	Salicional.....	73	"
14	8'	Vox Celeste, T. C.....	61	"
15	8'	Aeoline.....	73	"
16	4'	Flute Harmonique.....	73	"
17	4'	Fugara.....	73	"
18	8'	Oboe.....	73	"
19	8'	Vox Humana.....	73	"
20		Tremulant		

PEDAL ORGAN - Present Pipes and Chests

1-30 New 31-32

21	16'	Open Diapason.....	32	Pipes
22	16'	Bourdon.....	32	"
23	16'	Lieblich Gedeckt.....	32	Notes
24	8'	Violoncello.....	32	Pipes

COUPLERS

25	Swell to Great	30	Swell 4'
26	Swell to Great 4'	31	Swell 16'
27	Swell to Great 16'	32	Great 4'
28	Swell to Pedal	33	Great 16'
29	Great to Pedal	34	Swell Unison Separation

ADJUSTABLE COMBINATIONS

(Operated by pistons placed under respective manuals)

Pistons No. 1-2-3-4	Affecting Great and Pedal Stops
Pistons No. 1-2-3-4	Affecting Swell and Pedal Stops
Pistons No. 1-2-3-4-5	Affecting Full Organ

MECHANICALS

Voltmeter	Crescendo Indicator (Lights)	Sforzando Indicator (Light)
-----------	------------------------------	-----------------------------

PEDAL MOVEMENTS

Great to Pedal Reversible	Sforzando Pedal
Balanced Expression Pedal, Swell Organ	Organ bench with music shelf
Balanced Expression Pedal, Great Organ	Concave Pedal
Grand Crescendo Pedal	

- 2 -

#7024 - PRESBYTERIAN CHURCH, SHIPPENSBURG, PA.

The organ is to be removed from the church and returned to the factory of the party of the first part, and re-laid out, so that the front can be moved back to provide more choir space.

The action of the organ to be changed from the present tubular-pneumatic system to electro-pneumatic system.

All of the valves in the wind chest to be renewed, also on the wind chest primary stations, which incidentally are also to be changed to electro-pneumatic action.

An entirely new two-manual console to be provided.

A new motor generator set for action current to be furnished.

All of the reed pipes in the organ to be revoiced, with new tongues.

A new panel to be furnished in the present organ casing to close the opening where the console now is.

The pedal compass to be extended to 32 notes.

All of the metal stops to be equipped with modern slide tuners.

The Great organ to be enclosed in separate swell box.

A new tremulant to be provided.

The compass of Swell organ to be extended to 73 pipes.