# M. P. MÖLLER Organ Factory

5	2/12	and the second s	
Pipe Organ No	R=636	Date February 17, 1959	
	THE FIRST PRESBYTERIAN CHURCH,		
Action	Electro-Pneumatic	Console Detached-Rift Sown Oak	
Casing No.	Case Panel Only	Finish To Customer's Selection	
Decorations	Present - No Change	Motor Present Motor & Blower, New DC	
Width of Key-bed.	Standard	Motor Present Motor & Blower. New DC Organ Fower Unit Stop Controls Tilting Tablets	
No. Manuals		Wind Pressure 3½"	
To be Completed_	November 17, 1959	Blower Pipe furnished by Purchaser	
	SPECIFICAT	TIONS	
	FOR		
	REBUILDING PRESENT MOLLER OR	GAN OFUS 2068 - 1916 42563	
CONSOLE	Install new two manual electroconsole, pedal keyboard and or	-pneumatic detached tilting tablet gan bench.	
MANUAL CHEST	Releather 398 manual pipe pouches. Install 703 new stop action checks and eyelets. Install 305 new duplex shifters. Install 2 new single stop action rails. Install 5 new duplex stop action rails. Install new manual chest groove boards. Releather and electrify 12 stop action controls. Releather and electrify two 61 note primary stations.		
OFFSET ACTION	Releather and electrify Great (front pipe action)	8 Open Diapason action #1 to #17 inc.	
CONTACT BOX	Install new 17 note contact bo	x for offset action.	
PEDAL ORGAN	Releather and electrify 16 Bou Install new pipes and action f		
EXPRESSION	Install new accordian type exp	pression action.	
RESERVOIRS	Recover one (1) 2:-6" x 4:-6" Recover one (1) Pedal reservoi	•	
TREMOLO	Install one new electro-pneuma	tic beater type tremolo.	
PIPES	Install the following new pipe	981	
		- 44 pipes (#18 to #61 inc.) - 61 pipes	
	Install the following new pipe	es and action:	
		- 61 pipes and action - 183 pipes and action	

		_	-
ъ	-6	2	6
n	ACCRECATE TO	-	•

### THE FIRST PRESBYTERIAN CHURCH, JONESVILLE, MICHIGAN

SHEET 2

PIPES (cont'd)	Install modern tuning slides on all metal pipes. Repack wood stoppers on all wood pipes. Repair or replace all other damaged pipes.	
CABLES	Install new asbestos covered cables between console and organ.	
CASE PANEL	Install new case panel to enclose present console opening.	
ACTION CURRENT	Install new 10-15 Volt, 15 Ampere DC Organ Power Unit.	
BLOWER	Present blower and motor to be used without change.	
GENERAL.	The entire organ, except blower, is to be returned to factory of M. P. Moller, Inc. for rebuilding as specified above.	

# SPECIFICATIONS FOR CONSOLE AND ORGAN

MANUAL COMPASS PEDAL COMPASS WIND PRESSURE PITCH	CC to Cl, 61 notes CCC to G, 32 notes A-like @ 70°F
	GREAT ORGAN
1 8 2 8 3 8 4 8 5 8 6 4 7	Open Diapasonpresent pipes #1 to #17, new pipes  #18 to #61, present action
8 III	Mixture
9 8 10 8 11 8 12 8 13 8 14 4	Gedeckt

Tremulant

R-636		THE FIRST PRESBYTERIAN CHURCH, JONESVILLE, MICHIGAN SHEET 3
		PEDAL ORGAN (*)
16	16	Bourdonpresent pipes, present action #1 to #30 new pipes, new action #31 & #3232 Pipes
17	16	Lieblich Gedecktfrom #16
		(*) Provide slide in console to play Pedal Organ
		COUPLERS
18 19 20 21 22 23 24 25 26		Great to Pedal 4 Swell to Pedal 4 Swell to Pedal 4 Swell to Great 16 Swell to Great 4 Swell to Great 4 Great 16 Great 16 Great Unison Off
27 28 29 30		Great 4 Swell 16 Swell Unison Off Swell 4

## ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3 Pistons No. 1-2-3 Affecting Great and Pedal Stops Affecting Swell and Pedal Stops

#### PEDAL MOVEMENTS

1 - Great to Pedal Reversible

2 - Balanced Expression Pedal (8 contacts, reverse system)
3 - Balanced Crescendo Pedal with indicator light (green jewel)

#### ACCESSORIES

Concave and radiating pedal keyboard Organ bench with music shelf

Present motor and blower. New 10-15 volt, 15 ampere DC organ power unit.