

M. P. MÖLLER Organ Factory

2/11

Pipe Organ No. 8109 Date August 29, 1949
 For CONCORDIA EVANGELICAL LUTHERAN CHURCH, BERWYN, ILLINOIS
 Action Electro-pneumatic Console Detached
 Casing No. None Finish As per sample
 Decorations None Motor 1½ H.P., Style 3-P-2724
 Width of Key-bed Standard Stop Controls Stop Keys
 No. Manuals Two Wind Pressure Gt. 3½", Sw. 4", Ped. 4"
 To be Completed 12 to 15 Months Blower Pipe furnished by Purchaser

PITCH

A-440

SPECIFICATIONS

Great Organ

1	8'	Gedackt.....48.....35% tin....12 Zinc..S.M....73 pipes
2	4'	Prinzipal.....57.....18-19-½.....55% tin.....S.M....73 pipes
3	4'	Gemshorn.....from #8.....73 notes
4	2'	Waldflöte.....66-1/2.....45% tin.....S.M....61 pipes
5		Chimes.....(Deagan "D")....A to F.....#22 to #42....21 tubes
6		Tremolo

Swell Organ

7	8'	Rohrflöte.....52.....45% tin....12 Zinc..S.M....73 pipes
8	8'	Gemshorn (UNIT)....50-1/3.....45% tin....12 Zinc..S.M....85 pipes
9	4'	Nachthorn.....58....open metal.45% tin.....S.M....73 pipes
10	4'	Gemshorn.....from #8.....73 notes
11	III Rk.	Mixtur (12-15-19)....See Formula....45% tin.....S.M....183 pipes
12	8'	Fagott.....3-1/2".....73 pipes
13		Blank
14		Tremolo

Pedal Organ

15	16'	Sub Bass.....Large Ped. Bdn.....32 pipes
16	16'	Rohrgedackt...40.....12 pipes, 20 from #7....32 notes
17	8'	Rohrgedackt.....from #7.....32 notes
18	8'	Gemshorn.....from #8.....32 notes
19	4'	Rohrflöte.....from #7.....32 notes
20	III Rk.	Gemshorn Cornet (12-15-17)....from #8.....32 notes

Couplers

21	Great to Pedal	8'	26	Swell	16'
22	Great to Pedal	4'	27	Swell	8' Off
23	Swell to Great	16'	28	Swell	4'
24	Swell to Great	8'	29	Swell to Pedal	8'
25	Swell to Great	4'	30	Swell to Pedal	4'
			31	Great	16'
			32	Great	8' Off
			33	Great	4'

Adjustable Combinations

Pistons No. 1-2-3-4	Affecting Great and Pedal Stops
Pistons No. 1-2-3-4	Affecting Swell and Pedal Stops
Pistons No. 1-2-3-4	Affecting Entire Organ
General Cancel Piston	

Pedal Movements

Swell Expression Pedal
 Crescendo Pedal, with indicator lights
 Great to Pedal Reversible, manual piston and toe stud
 Chorale Reversible Piston (built in manner of Sforzando, to be wired after installation) with indicator light

Accessories

Organ Bench with Music Shelf and Back Rest
 Electric motor, Kinetic Blower, action current generator of ample capacity.
 Concave, Radiating Pedal Clavier

SIGNAL LIGHT

SIGNAL BUTTON

General

Curtains to be hung from Great and Pedal chests (front and sides); Swell Organ to be concealed in this manner below Great, with Pedal flanking Great chest on each side. Exposed pipes to be tuned or slotted in backs, and exposed wood work to be finished in an artistic manner.

Upon completion, the organ is to be subject to the examination and approval of Paul G. Bunjes, who is acting as consultant to the purchaser; in the event of his inability to function in this capacity, an alternate acceptable to both parties is to be chosen. Copies all data, scalings and drawings are to be sent to Mr. Bunjes at 507 Fifth Street, Wausau, Wisconsin.

Swell Mixture Formula

12	8	1
15	12	8
19	15	12
1-21	22-45	46-61
C to G#	A to G#	A to C
21	24	16