

M. P. MÖLLER Organ Factory

2/15

Pipe Organ No.	R-891	Date	April 21, 1973
For	ST. PETER'S EPISCOPAL CHURCH, ROME, GEORGIA		
Action	Electro-Pneumatic	Console	Present - Detached
Casing No.	None	Finish	Present - No Change
Decorations	Present Display Pipes - no change	Motor	Present Motor and Blower
Width of Key-bed	Standard	Stop Controls	Stop Keys
No. Manuals	TWO AND PEDAL	Wind Pressure	
To be Completed	Soon as Possible	Blower Pipe furnished by	Purchaser

SPECIFICATIONS

FOR

REBUILDING, CHANGING TONALLY, AND ADDING TO PRESENT
MOLLER ORGAN OPUS 7880 - 1949

CONSOLE

Reuse present two manual, electro-pneumatic, detached stop key type console, pedal keyboard and organ bench with the following improvements:

Replace plastic parts on face of console as follows:

- 43 stop keys
- 16 combination and reversible pistons
- 9 name strips
- 1 factory nameplate

Repair or replace seriously worn or damaged parts.
Clean mechanism and adjust contacts throughout.

MANUAL CHESTS

Recover 620 manual pipe pouches.
Install 654 new stop action checks and eyelets.
Install 248 new duplex shifters.
Recover two 73 note primary stations and install new magnet plugs and armatures.
Recover 10 stop action primaries and install new magnet plugs and armatures.
Recover 8 Trompette pedal primary #1-44 and install new magnet plugs and armatures.
Rework or install new toeboard/rackboard assemblies as required for tonal changes.

OFFSET AND UNIT ACTIONS

Recover the following actions and install new magnet plugs and armatures:

- Great 8 Diapason - #1-12
- Swell 16 Gedeckt - #1-85
- Swell 4 Prestant - #1-73

Install new action for the following:

- Great III Mixture - #1-61
- Swell 4 Harmonic Flute - #1-73
- Swell ~~2/3 Quint~~ - ~~#2-63~~

8 Gamba #1-# 73

CONTACT BOXES Install new single conductor contact box for Great 8 Diapason #1-12.
Recover Swell 73 note contact box and install new silver wire contacts.

SWITCHES Install new switches with stop actions for the following:

Great	III	Mixture	61 notes
Swell	16	Gedeckt	73 notes
Swell	8	Gedeckt	73 notes
Swell	4	Prestant	73 notes
Swell	4	Harmonic Flute	73 notes
Swell	2	Octavin	61 notes
Swell	16 8	Gamba <i>Gamba</i>	73 notes
Swell	8	Trompette	44 notes

PEDAL ORGAN Recover the following actions and install new magnet plugs and armatures:

16	Subbass	32 notes
8	Octave	44 notes

Install new action for the following:

8	Octave	12 notes
16	Contre Trompette	12 notes

Install new 32 note relay with necessary switches.

EXPRESSION Recover two 16 note expression actions and install new magnet plugs and armatures.
Recover 32 shade pneumatics.
Install 32 new shade jacks and connecting rods.
Refelt shades.

RESERVOIRS Recover the following reservoirs and install new curtain valves as required:

Two 2'-6" x 4'-0" manual
Two 1'-6" x 2'-6" pedal
One 1'-6" x 2'-0" pedal
One 1'-9" x 2'-6" expression
One 3'-0" x 3'-0" blower

TREMOLOS Install two new electro-pneumatic tremolos.

PIPES

Revoice Swell 8 Trompette - 85 pipes.
 Repack all present wood pipe stoppers.
 Install the following new pipes:

Great	8	Rohrflöte	85 pipes
Great	2	Blockflöte	61 pipes
Great	III	Mixture	183 pipes
Swell	4	Prestant	73 pipes
Swell	2-2/3 2-2/3	Quint Nasat TC	61 pipes
Pedal	8	Octave	12 pipes
Pedal	16	Contre Trompette	12 pipes

CABLES

Install new plastic covered cables between console and organ.
 Install new action current wires between console, organ and power unit.

ACTION CURRENT

Install new 10-15 Volts, 30 Amperes DC organ power unit.

BLOWER

Reuse present 2 HP, Style 3-P-3025 motor and blower without change.
 Install new 12" diameter flexible connection with draw bands.
 Install new motor-blower coupling leathers.

GENERAL

Entire organ (except display pipes and blower) to be returned to the factory of M. P. Möller, Inc. at Hagerstown, Maryland for rebuilding as specified above.

SPECIFICATIONS
 FOR
 CONSOLE AND ORGAN

MANUAL COMPASS: CC to C4, 61 notes
 PEDAL COMPASS: CCC to G, 32 notes
 WIND PRESSURE:
 PITCH: A-440 @ 70°F

GREAT ORGAN 7
 Enclosed

1	8	Diapason.....	present pipes and action.....	73 pipes
2	8	Rohrflöte.....	new pipes; present Melodia action....	85 pipes
3	4	Octave.....	present pipes and action.....	73 pipes
4	4	Flöte.....	from #2.....	73 notes
5	2	Blockflöte.....	new pipes; present Dulciana action...	61 pipes
6	III	Mixture.....	new pipes and action.....	183 pipes
7		Tremolo		
8		Blank		
9		Blank		

SWELL ORGAN 4

Enclosed

10	16	Gedeckt.....present pipes and action.....85 pipes
11	8	Gamba.....present pipes and ^{new} action.....73 pipes
12	8	Gedeckt.....from #10.....73 notes
13	4	Prestant.....new pipes; present Flute Harmonic action.....73 pipes
14	4	Harmonic Flute.....present pipes; new action.....73 pipes
15	2	Octavin.....from #13.....61 notes
16	1-1/3	Quint..... new pipes and action from #15A.....61 pipes
17	8	Trompette.....present pipes and action.....35 pipes
18	4	Clairon.....from #17.....73 notes
19		Tremolo
20		Blank
21		Blank
22		Blank
15A	2-2/3	Nasat TC new pipes, present Gamba action 61 pipes

* PEDAL ORGAN 2

23	16	Subbass.....present Bourdon pipes and action.....32 pipes
24	16	Gedeckt.....from #1032 notes
25	8	Octave.....present pipes and action #1-44; new pipes and action #45-56.....56 pipes
26	8	Gedeckt.....from #10.....32 notes
27	4	Octave.....from #24.....32 notes
28	4	Gedeckt.....from #10.....32 notes
29	2	Octave.....from #24.....32 notes
30	16	Contre Trompette...new pipes and action #1-12; 20 from #17.....32 notes
31	8	Trompette.....from #17.....32 notes
32	4	Clairon.....from #17.....32 notes

(*) Pedal organ playable thru new relay and switches.

COUPLERS

No Change

ADJUSTABLE COMBINATIONS

No Change

PEDAL MOVEMENTS

No Change

ACCESSORIES

Present concave, radiating pedal clavier
 Present organ bench with music shelf
 Present motor and blower
 New DC organ power unit

5/10/73

RVK/mr