M. P. MÖLLER Organ Factory

Width of Key-bed Stop Controls No. Manuals Wind Pressure To be completed Dec 1, 1924. Blower pipe furn Pitch 1440 SPECIFICATIONS: Organ on 5 wind are except 16 Trombone, which GREAT OFGAN 16 Double Open Dispason. One 17 Depoil Flue 18 Dolo. Octave 19 Dolo. Octave 10 September 1990 11 September 1990 12 September 1990 13 Games Flore 14 September 1990 15 STELL ORGAN STELL ORGAN STELL ORGAN 15 September 1990 16 September 1990 17 September 1990 18 September 1990 18 September 1990 18 September 1990 1990 1990 1990 1990 1990 1990 1990	24.
Casing of Finish Decorations Dall Gold Bronze Motor Width of Key-bed Stop Controls No. Manuals Wind Pressure To be completed Doc 1, 1924. Blower pipe furn SPECIFICATIONS: Organ on 5 and Section 16 Transpace Completed Doc 1, 1924. Blower pipe furn SPECIFICATIONS: Organ on 5 and Section 16 Transpace Completed Doc 1, 1924. Blower pipe furn SPECIFICATIONS: Organ on 16 Transpace Completed Doc 1, 1924. Blower pipe furn SPECIFICATIONS: Organ on 5 and Section 16 Transpace Completed Doc 1, 1924. Blower pipe furn SPECIFICATIONS: Organ on 5 and Section 16 Transpace Completed Doc 1, 1924. Blower pipe furn SPECIFICATIONS: Organ on 5 and Section 16 an	
Decorations Dell Gold Bronzo Motor Stop Controls No. Manuals Specifications: Specific	
Vidth of Key-bed Stop Controls No. Manuals Wind Pressure To be completed Dec. 1, 1924. Blower pipe furn SPECIFICATIONS: Organ on 5 and Section 16 Transon Chart ORGAN Double Open Dispason Octave Controls Wind Pressure Chart ORGAN Double Open Dispason Octave Controls Wind Pressure Chart ORGAN Controls Wind Pressure SPECIFICATIONS: Open Dispason Octave Controls Wind Pressure Chart ORGAN Controls Wind Pressure SPECIFICATIONS: Controls Wind Pressure Chart ORGAN Controls Wind Pressure C	
Width of Key-bed Stop Controls No. Manuals Wind Pressure To be completed Dec 1, 1924 Blower pipe furn SPECIFICATIONS: Organ on 5 wind and one of the complete of the compl	lectric
No. Manuals Wind Pressure To be completed Dec. 1, 1924 Blower pipe furn SPECIFICATIONS: Organ on 5 wind ares except 16 frombone, which GREAT ORGAN Double Open Dispessor	raw knobs
SPECIFICATIONS: Organ on 5 wind area except 16 Trombone, which GREAT ORGAN 1 16 Double Open Dispason	
Pitch 1-440 Organ on 5 wind area except 15° Trombone, which GREAT ORGAN 1 16° Down 16 Open Diapason	
Organ on 5" wind sugar except 16° Trombone, which GHEAT ORGAN 1	nsnea by
1 16* Down Diapason	is on 10"
14 16 Bourdon	1) 73 # 1) 73 # 1) 73 # 1) 73 # 1) 73 # 1) 73 # 1) 73 # 1) 73 # 1) 73 # 1) 73 # 1) 73 #
Open Diapason	1 73 Pines
) 73 #
28 80 Melodia	
29 80 Dulciana	
27 80 Violin Diapason	···· 73
PEDAL ORGAN	1
34 16* Open Diapason	14 32 Notes ipas. 32 Notes pipas. 32

```
COUPLERS
      Great to Pedal42
41
42
       Great to Pedal 41
       Swell to Pedal
43
44
      Swell to Pedal 4*
     Choir to Pedal
45
      Choir to Pedal 4*
46
      Pedal Octave
47
48
      Great 49
      Great 16?
49
50
      Swell to Great
      Swell to Great 41
51
      Swall to Great 16*
52
      Choir to Great
53
54
      Choir to Great 47
      Choir to Great 16*
55
      Swell 41
56
      Swell 167
57
      Choir to Swell 41
58
      Choir to Swell 161
59
60
      Choir 41
61
      Choir 161
      Swell to Choir
Swell to Choir 4
62
      Swell to Choir 4'
Swell to Choir 16'
63
64
      Choir to Swell
65
      Great Tremlant
Swell Tremlant
66
67
      Choir Tremlant
68
      Great Unison Cancel - placed in key Jamb
Swell Unison Cancel - placed in key Jamb
      Choir Unison Cancel - placed in key Jamb
```

ADJUSTABLE COMBINATIONS

(Operated by pistons placed under respective marmals.) Pistons No. 1-2-3-4-5-6 Affecting Swell & Pedal Stops Pistons No. 1-2-3-4-5-6 Affecting Great & Pedal Stops Pistons No. 1-2-3-4-5-6 Affecting Choir & pedal Stops Pistons No. 1-2-3-4-5 Affecting Full Organ

PEDAL MOVEMENTS

Swell to Pedal Reversible Great to Pedal Reversible

Balanced Swell Organ Expression Pedal

Balanced Great-Choir Organ Expression Pedal

Grand Crescendo Pedal (Adjustable) and indicator Sforzando Pedal and Indicator

Action Current Indicator

Organ Bench with Music Shelf. Concave Pedal. El ectric motor, blower and generator of ample capacity.

DETAILS

The party of first part agrees to rebuild the present organ in the First Pres. Church, Jersey City, N.J., in accordance with the attached specifications, using only the present old pipes and case. The party of the first part is to extend the present case on both ends matching the wood, design and finish to conform with the already existing case, and to submit blue print for approval, showing exterior of case, and layout of organ as it will appear, and to redecorate front pipes in dull gold bronze, samples first to be submit ted to party of second part for approval.

DETAILS CONTINUED

Wood and finish of console is to match the case, and to
be placed in a position agreeable to party of second part,
with a maximum distance of ten feet (10°) from organ,
DRAWKNOBS: to be of small type
COUPLERS: Controlled by tablets above the manuals,
All old pipes to be thoroughly gone over, revoiced and the
present tone is to be retained as near as possible,
All material and workmanship to be of the highest
quality, and to be done in the best workmanshiplike manner,