THE REUTER ORGAN COMPANY LAWRENCE, KANSAS

PROPOSES A TWO MANUAL PIPE ORGAN

FOR

ST. PETER'S LUTHERAN CHURCH DESHLER, NEBRASKA

NOVEMBER 27, 1967

Mr. Frank R. Green Home Office Sales Representative and Designer

THE Peuter ORGAN COMPANY

GENERAL SPECIFICATIONS

INSTALLATION

MANUALS Compass CC to C4, 61 Notes.

PEDAL Compass CCC to G, 32 Notes.

REGISTRATION Controlled by Stop-Keys.

CONSOLE Detached, placed where desired in choir gallery; wood and color-finished to

church's sample.

KEY ACTION Reuter's simulated tracker touch, (double spring type).

(double spring type).

PITCH A-440.

CASEWORK OR GRILLE None, except that for console.

SWELL BOX or EXPRESSION To be furnished and installed by The ENCLOSURE Reuter Organ Company; the said swell

box or expression enclosure to be hardwood faced, and painted a color harmonious to its' surroundings. The

said swell box or expression enclosure will utilize a corner position of the organ area, thus incorporating the back

complete the enclosure for those stops designated as being under expression.

and side walls of the organ area to

The organ is to be installed in the space now occupied by the present pipe organ. The purchaser is to remove the present grille entirely, to thus provide

improvements deemed necessary by The Reuter Organ Company to enhance the acoustical environment of the choir gallery and organ area will be

a free-standing organ installation.

accomplished by the Church at its' expense, but in accordance with the recommendations made by The Reuter Organ

Company, prior to the installation of

the organ.

GREAT ORGAN (Displayed and free standing)

1.	81	Prinzipal	61 pipes.
2.	81	Bordun (Metal)	61 pipes.
3. •	81	Spitzflöte	61 pipes.
4.	4'	Oktav	61 pipes.
5.	21	Hohlflöte	61 pipes.
6.	III	Mixtur	183 pipes.
7. *	8'	Oboe Schalmey	61 pipes.
		Chiman (Canada D	

Chimes (Console Preparation Only)

Couplers to Great:

Great to Great 16t

Great Unison Off

Great to Great 4'

Swell to Great 16"

Swell to Great 8'

Swell to Great 4'

* The stops so designated will be installed in the Swell Organ expression enclosure and expressive when the Swell pedal is engaged.

THE Peuter ORGAN COMPANY

SWELL ORGAN (Expressive)

8.	g.	Gedackt	
	•	Gedackt	61 pipes.
9.	8	Gemshorn	61 pipes.
10.	81	Gemshorn Celeste (GG)	54 pipes.
11.	41	Nachthorn	61 pipes.
12.	2 2/3'	Nazard	61 pipes.
13.	2'	Prinzipal	61 pipes.
14.	1 3/5'	Terz	61 pipes.
15.	1 1/3'	Quint	61 pipes.
16.	1"	Sifflöte (Harmonic)	61 pipes.
17.	81	Trompete TRemolo	61 pipes.
		Couplers to Swell:	

Swell to Swell 16'

Swell Unison Off

Swell to Swell 4'

PEDAL ORGAN (# to be functionally displayed, free-standing)

- 18. # 16' Prinzipal 44 Pipes.
- 19. 16' (Sw) Bordun 56 Pipes.
- 20. # 8' Oktav
- 21. 8' (Sw) Bordun °
- 22. # 4' Choral Bass 44 Pipes.
- 23. 4' (Sw) Bordun
- 24. # 2 Choral Oktav
- 25. # II Rauschquint 64 Pipes.
- 26. 16' (Sw) Kontra Trompete (½L) 12 Pipes.
- 27. 8' (Sw) Trompete
- 28. 4' (Gt) Oboe Schalmei

Couplers to Pedal:

Great to Pedal 8'

Great to Pedal 4'

Swell to Pedal 8'

Swell to Pedal 4'

ADJUSTABLE COMBINATIONS

Operated by thumb and toe pistons as indicated below. Adjustable at keyboard and visibly affecting stop controls.

Four thumb pistons acting on Great stops and couplers.

Four thumb pistons acting on Swell stops and couplers.

Four toe pistons acting on Pedal stops and Manual to Pedal couplers.

Four thumb pistons acting on all stops and couplers, duplicated on toe pistons.

General Cancel, thumb piston.

COMBINATION COUPLERS

Pedal Combinations to Great pistons, On-Off.

Pedal Combinations to Swell pistons, On-Off.

REVERSIBLES

Great to Pedal, duplicated on thumb piston.

Swell to Pedal, duplicated on thumb piston.

Tutti, duplicated on thumb piston.

PEDAL MOVEMENTS

Balanced expression pedal for Swell Organ and those stops of the Pedal designated (Sw.).

Register Crescendo Pedal.

ACCESSORIES

Current Indicator Light, green.

Crescendo Indicator Light, amber.

Tutti Indicator Light, red.

Organist's Bench, with curved front, adjustable in height.

Organ Bench back rest, model 1275.

Solid wood music rack, with built-in at base, fluorescent light.

Concave, radiating pedal keyboard, A.G.O. Model.

Pedal keyboard light, concealed type.

The Church's new 2 H. P. Spencer Steel Orgoblo to be reused, as is.

The Church's present and new rectifier to be reused, as is.

The Reuter Organ Company to furnish and install a static pressure reservoir on existing blower at the time of installation of the new organ.

Concussion winkers for stabilized air pressures at all times.

Two Pedal Reservoirs.

"Organ Construction Details" Form 7 (8/67-1.5M) part of contract

THE REUTET ORGAN COMPANY