M. P. MÖLLER Organ Factory

	3/23	mara-uniteriteration		
Pipe Organ No	R-108	November 12, 1979		
To:	ST. JOHN'S UNITED CHURCH OF CHRIST, WHEELING, WEST VIRGINIA			
Action	Electro-pneumatic	Console Detached - with roll top		
Casing No.	Present - no change	Finish To customer's sample		
Decorations	None	Motor Present Spencer		
Width of Key-bed	Standard	Stop Controls Draw Knobs & Tilting Table		
No. Manuale	THREE AND PEDAL	Wind Pressure 35" 4"		
To be Completed.	November 1, 1980	Blower Pipe furnished by Purchasing		
	SPECIFICA			
	FOR			
	REBUILDING AND CHANGI PRESENT E. M. SKINNER ORGAN			
CONSOLE	Install new three manual, electro-pneumatic, detached draw knob style console, pedal keyboard and organ bench.			
MANUAL CHESTS	Recover 1091 manual pipe pouches. Install 1091 stop action checks and eyelets. Recover three 61 note primary stations and install new magnets. Recover 17 stop action primaries and install new magnets. Rework and/or install new toeboard/rackboard assemblies as crequired for tonal changes. Coney. offset talle Kolin to pape hales for scale 1'z Larg at *1- Lingly Delde & Drancipal Recover the following actions and install new magnets.			
OFFSET & UNIT	Recover the following actions (eliminate all tubed action	s and install new magnets.		
	GREAT ORGAN			
	8 Principal 8 Bourdon 4 Octave	12 notes 12 notes 10 notes		

8	Principal	12 n	otes
8	Bourdon	12 n	otes
4	Octave	1.0 n	otes
	SWELL ORGAN		
8	Rohrflöte	12 n	otes
8	Viole	12 n	otes
88	Celeste TC		otes
B.	Principal	-	otes
1-1/3	larigot		otes
	CHOIR ORGAN		
8	Holzgedeckt	12 n	otes

SWITCHES Install electro-pneumatic switches with stop actions and diodes as required.

PEDAL ORGAN Recover the following actions and install new magnets:

16 Subbass 44 notes 8 Principal 61 notes

Install new 32 note relay with necessary switches.

EXPRESSION Recover two whiffletree shade actions.

Refelt shades.

RESERVOIRS Recover the following reservoirs and install new curtain valves required:

Three 3'-0" x 5'-0" One 2'-6" x 4'-0" One 2'-0" x 3'-0"

TREMOLOS Install new electro-pneumatic tremolos.

PIPES Install new pipes as indicated by specifications.

Revoice all pipes being reused. Install slide tuners as required. Repack all wood pipe stoppers.

CABLES Install new plastic covered cables between console and organ.
Install new action current wires between console, organ and

DC organ power unit.

ACTION CURRENT Install new 10-15 volts, 30 amperes DC organ power unit.

BLOWER Reuse present Spencer motor and blower without change.

Install new 15" and 3" diameter flexible connections with draw bands.

Church to develop room with filtered air intake.

GENERAL All parts specified above to be rebuilt to be returned to the form of M. P. Moller, Inc. at Hagerstown, Maryland.

Harp, Console, and selected wood pipes to remain in the church their property.

All other parts from present instrument not required to complet program become the property of M. P. Möller, Inc.

SPECIFICATIONS FOR CONSOLE AND ORGAN

PEDA	IAL COMPASS L COMPASS PRESSURE TH	CC to C4, 61 notes CCC to G, 32 notes A-440 @ 70°F
,		GREAT ORGAN - Enclosed with Choir 8
1 2 3 4 5	8 8 4 2 111-IV	Principalnew pipes; present 8 2nd Open Diapason action61 pipes Bourdonnew pipes; present 8 Gross Flute action61 pipes Octavenew pipes; present 8 Flute Celeste II action61 pipes Waldflötenew pipes; present 4 Harmonic Flute action61 pipes Fourniturenew pipes; present 8 Cornopean action220 pipes Chimespresent Deagan "D" tubes; new electric actions, transformer, relays and volume control A to F, #22 to 42
7		Tremolo SWELL ORGAN - Enclosed 9
8 9 10 11 12 13 14 15 16	8 8 8 4 2 1-1/3 II 8	Rohrflötenew pipes; present 16 Bourdon action
		CHOIR ORGAN - Enclosed 4
17 18 19 20 21	8 4 2 8	Holzgedeckt#1-12 present 8 Concert Flute pipes, #13 up present 4 Flute d'Amour pipes; present 8 Concert Flute action
		* PEDAL ORGAN - Unenclosed 2
22 23 24 25 26 27 28 29	16 8 8 4 III	Subbasspresent 16 Bourdon pipes & action
	4 6/4644	Construction of the second sec

COUPLERS

to the same of the				
30	Great to Pedal	41	Swell to Choir	16
31	Swell to Pedal	42	Swell to Choir	
32	Swell to Pedal 4	43	Swell to Choir	4
33	Choir to Pedal	44	Great Unison O	ff
34	Choir to Pedal 4	45	Great 4	
35	Swell to Great 16	46	Swell 16	
36	Swell to Great	47	Swell Unison O	ff
37	Swell to Great 4	48	Swell 4	
38	Choir to Great 16	49	Choir 16	
39	Choir to Great	50	Choir Unison O	ff
40	Choir to Great 4	51	Choir 4	

ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3	Affecting Great
Pistons No. 1-2-3	Affecting Swell
Pistons No. 1-2-3	Affecting Choir
Toe Studs No. 1-2-3	Affecting Pedal
Pistons No. 1-2-3-4-5-6	Affecting Full Organ
General Cancel	

PEDAL MOVEMENTS

Great to Pedal reversible
Sforzando reversible with indicator light (red jewel)
Balanced Expression Pedal - Great-Choir Organs (16 contacts, make to open)
Balanced Expression Pedal - Swell Organ (16 contacts, make to open)
Balanced Crescendo Pedal with indicator light (green jewel)

ACCESSORIES

Concave, radiating pedal clavier
Organ bench with music shelf
Transparent music rack with light
Pedal light
Present motor and blower
New DC organ power unit
Present motor starter switch

RVK/mr 4/17/80