M. P. MÖLLER Organ Factory

		- Control Cont	
Pipe Organ No	M-4875	_DateJuly	15, 1987
For	FIRST PRESBYTERIAN CHURCH, ENGL		
Action	Electro-Pneumatic		ent - Detached
Casing No.	Present		ange
Decorations	None	Finish No character Present 2 HP Present 15 H	P - 3P-3328 (Ant.) P - 6P-3330 (Main)
Width of Key-bed_	Standard - Tracker Touch		
No. Manuals	FOUR - Tilted	Wind PressureGr3.1	3 1/2" & 8" 72" SwGCh4" Ped3 1/2 485
To be Completed_		Blower Pipe furnish	
PITCH: A-440	SPECIFICATI		
	FOR REFINISHING PRESENT MOLLER OR	GAN OPUS 10175-1966	36587
GREAT ORGAN	Install 12 new pipes (#50-61) o Raise pitch in upper end of III doubling of the low-pitched M	Rks. Cymbel by usi	cale) ng
SWELL ORGAN	Deslot 8' Viole d' Gamba from 4' C up Deslot 8' Viole Celeste from 4' C up Install 12 new pipes (#50-61) of 2' Weitprincipal (rescale) Install 12 new pipes (#45-56) of 1 3/5' Tierce		
CHOIR-POSITIV ORGAN	Deslot 8' Viola Pomposa from 4' C up Deslot 8' Spitz Viole Celeste from 4' C up Deslot 8' Klein Erzahler from 4' C up Deslot 8' Klein Erzahler Celeste Deslot 4' Spitzprincipal Install 12 new pipes (#50-61) of 2' Octave (rescale) Install 12 new pipes (#45-56) of 1 1/3 Larigot (rescale) Install 12 new pipes (#43-54) of 1' Sifflote (rescale)		
SWELL & CHOIR - POSITIV EXPRESSION ENCLOSURES	Replace individual expression pneumatics with accordion type expression motors (2 motors for each expression enclosure), including necessary traces and miscellaneous hardware.		
GENERAL	Tone finish and regulate entire	organ by Head Fact	ory Finisher.
CONSOLE	Install new switches on express	ion pedals	
dmm			

49887 U S

7-30-87