K.M.Mäller

M. P. MÖLLER Organ Factory

8		REVISED APRIL 20, 1977
Pine Grean No	R=954	Date February 9, 1976
For	ST. PAUL UNITED	METHODIST CHURCH, CHAMBERSBURG, PENNSYLVANIA
Action	Electro-Pneumatic	Oonsole Present-Detached
Casing No.	Present Grilles	Finish No Change
Decorations	None	Motor Present 3 H.P., Style 3-P-3027
Width of Key-bed.	Standard	Stop Controls Draw Knobs & Tilting Tablets
No. Manuals	THREE AND PEDAL	Wind Pressure and the second s
To be Completed_	July 1, 1977	Blower Pips furnished by Purchaser

BPECIFICATIONS

FOR

REBUILDING, CHANGING TONALLY AND ADDING TO PRESENT MOLLER ORGAN OPUS 7288 - 1947 24622 3/16

CONSOLE

Reuse present console, rebuilding same as follows:

Replace all stop and coupler contacts.

Replace all stop and coupler pneumatics.

Replace two reversibles.

Replace all coupler and combination primaries and install new magnet plugs and armatures.

Replace all combination piston buttons and springs.

Replace crescendo and expression pedal pads and edging.

Replace burrs and felt washers on manual keys

Refelt console action as required.

Replace all pedal key caps.

Refelt pedal keyboard and install new insulating bushings.

Install new terrace with duplicate general toe studs.

Recover console reservoir.

Recover roll top.

Clean and polish cabinet, bench and pedal keyboard.

MANUAL CHESTS

Recover 946 manual pipe pouches.
Install 1185 stop action checks and eyelets.
Install 227 duplex shifters.
Recover four 73 note primary stations and install new magnet armatures.
Recover 17 stop action primaries and install new magnet armatures.
Recover one 8 note pedal primary.
Rework and/or provide new toeboard/rackboard assemblies as required for tonal changes.

Lawless & Associates 3n 750 Nortand Ac 1720 OFFSET & UNIT ACTIONS

Recover the following actions and install new magnet armatures:

Great	8	Principal	12 notes
Swell	16	Bass Gedackt	97 notes
Swell	8	Salicional	8 notes
Swell	4	Spitzprincipal	8 notes

Install new action for Choir 1-1/3 Quintfibte - 61 notes. Unify Swell 8 Trompette action #1-20.

CHIMES

Recover 21 note chimes action and install new magnet armatures.

CONTACT BOXES

Recover Swell 73 note contact box and install new silver wire contact blocks.

Recover single conductor contact box for Great

Principal #1-12.

SWITCHES

Recover electro-pneumatic switches and stop actions for the following:

Great station cutout - front Great station cutout - rear Great chimes Swell 16 Bass Gedackt Swell 8 Gedackt Swell 8 Salicional Swell 4 Spitzprincipal Swell 4 Flute	73 notes 73 notes 21 notes 73 notes 73 notes 8 notes 8 notes 73 notes
	73 notes 61 notes 61 notes

Install new electro-pneumatic switches with stop actions for:

20 notes Swell 8 Trompette

61 notes Choir 1-1/3 Quintflote

Recover the following actions and install new magnet armatures: PEDAL ORGAN

> 16 Principal 12 notes 16 Subbass 56 notes

EXPRESSION

Recover one 18 note and one 14 note expression action and install new magnet armatures.

Recover 32 shade and bumper pneumatics.

Install 32 new shade jacks and connecting rods.

Refelt shades.

RESERVOIRS

Recover the following reservoirs and install new curtain valves as required.

One 3'-0" x 4'-0" menual One 2'-6" x 4'-0" manual

One 1'-6" x 2'-6" pedal Two 1'-6" x 2'-0" pedal

Two expression

One 3'-0" x 3'-0" blower

TREMOLOS

Install two new electro-pneumatic tremolos.

PIPES

Install the following new pipes:

Great	8 Princip	pal		pipes
Great	8 Rohrfl	dte	73	pipes
Great	4 Octave		73	pipes
Great	2 Flachf		61	pipes
	II-IV Mixtur		208	pipes
Swell		rincipal	73	pipes
Choir	4 Spitzf		73	pipes
	-1/3 Quintf		61	pipes
		Trompette (1/2	L) 12	pipes

Revoice all pipes being reused. Repack all wood pipe stoppers.

CABLES

Install new plastic covered cables between console and organ. Install new action current wires between console, organ and DC organ power unit.

ACTION CURRENT

Install new 10-15 volts, 30 amperes DC organ power unit.

BLOWER

Reuse present 3 HP, Style 3-P-3027 motor and blower without change. Install new blower-motor coupling leathers.

Install new 12" diameter flexible connection with draw bands.

GENERAL.

All parts specified above to be returned to the factory of M. P. Möller, Inc. at Hagerstown, Maryland.

All parts from present instrument not required to complete this program become the property of M. P. Möller, Inc.

SPECIFICATIONS
FOR
CONSOLE AND ORGAN

MANUAL COMPASS PEDAL COMPASS WIND PRESSURE PITCH CC to C4, 61 notes CCC to G, 32 notes

A-440 @ 70°F

GREA	T ORGAN		Enclosed	with	Choir	8
------	---------	--	----------	------	-------	---

1 2 3 4 5 6 7	8 8 4 2 111-IV	Principalnew pipes; present Diapason action
2		Tremolo

SWELL ORGAN - Enclosed 5

		market and the second s	M VINEY - LAKE	.0364 -	
9 10 11 12 13 14 15 16 17 18	16 8 8 8 4 4 2-2/3 2 8	Gedackt framework framewor	rom #9t pipes; and act pipes; and act pes; present 8 rom #9	ckt pipes and action	o notes pipes pipes pipes pipes notes notes notes
		CHO	IR ORGAN - Enc.	losed 5	
19 20 21 22 23 24 25 26	8 8 4 2 1-1/3 8	Dolcepresen Dolce Celeste TC presen Spitzflötenew pi Flachflötef Quintflötenew pi Cor Anglaispresen Tremolo	t Great Dulcian t Unda Maris popes; present 8 from #5 pes and action t pipes and ac	na pipes and action	1 pipes 3 pipes 1 notes 1 pipes
		* PED	AL ORGAN		
27	16	Principal12 prese	nt Diapason pi m #1	pes and action;	2 notes
28 29 30 31 32	16 16 8 4 16	Subbasspresen Bass Gedacktf Gedacktf	t Bourdon pipe from #9 from #9 from #28	s and action	6 pipes 62 notes 62 notes 62 notes
		(*) Pedal Organ pl (rewire as req		esent slides in console	
		C O	UPLERS		
33 34 35 36 37 38 39 40 41 42 43	Swell to Choir to Swell to Swell to Choir to Choir to	Pedal 4 Pedal 4 Pedal 4 Pedal 4 Pedal 6 Pedal 6 Pedal 6 Pedal 6 Pedal 6 Pedal 6 Pedal 7 Pedal 7 Pedal 8 Pedal 8 Pedal 8 Pedal 8 Pedal 9 Pedal	44 45 46 47 48 49 50 51 52 53	Swell to Choir 16 Swell to Choir Swell to Choir 4 Great 16 Great 4 Swell 16 Swell Unison Swell 4 Choir 16 (provide jamb swi	t c h)

ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3-4-5	Affecting Great
Pistons No. 1-2-3-4-5	Affecting Swell
Pistons No. 1-2-3-4-5	Affecting Choir
Pistons No. 1-2-3-4-5	Affecting Pedal (duplicated by toe studs)
Pistons No. 1-2-3-4-5	Affecting Entire Organ (duplicated by toe studs)
General Cancel	

PEDAL MOVEMENTS - no change

Great to Pedal reversible
Balanced Expression Pedal - Great and Choir Organ (18 contacts - regular system)
Balanced Expression Pedal - Swell Organ (14 contacts - regular system)
Balanced Crescendo Pedal - Entire Organ - with disc indicator
Sforzando reversible - duplicated by manual piston - with indicator light (red jewel)

ACCESSORIES

Concave, radiating pedal clavier Organ bench with music shelf Music rack DC indicator light Present motor and blower New DC organ power unit

RVK/mr 4/5/76 REVISED 4/20/77