

M. P. MÖLLER Organ Factory

217

R-634

Pipe Organ No. R-634 Date January 19, 1959
 For ST. MARY'S R. C. CHURCH, LAUREL, MARYLAND 1506
 Action Electro-Pneumatic Console Detached
 Casing No. Present - No Change Finish To Customer's Selection
 Decorations Present - No Change Motor Present Motor & Blower. New DC
 Width of Key-bed Standard Stop Controls Tilting Tablets Organ Power Unit
 No. Manuals Two and Pedal Wind Pressure _____
 To be Completed September 19, 1959 Blower Pipe furnished by Present - No Change

SPECIFICATIONS

FOR

REBUILDING PRESENT MOLLER ORGAN OPUS 4129 - 1925 45069

CONSOLE Install new two manual electro-pneumatic detached tilting tablet console, pedal keyboard and organ bench.

MANUAL CHEST Releather 354 manual pipe pouches.
 Install 537 new stop action checks and eyelets.
 Install 183 new duplex shifters.
 Releather and electrify 9 stop action controls.
 Releather and electrify two 61 note primary stations.

OFFSET ACTION Releather and electrify Great 8 Open Diapason action #1 to #17 inc. (front pipe action).

CONTACT BOX Install new 17 note contact box for Great 8 Open Diapason.

PEDAL ORGAN Releather and electrify 16 Bourdon action #1 to #32 inc.

EXPRESSION Install new accordian type expression action.

RESERVOIR Recover one 2'-6" x 4'-0" Manual reservoir.
 Install new 1'-6" x 2'-6" Pedal reservoir.

TREMOLO Install new electro-pneumatic tremolo.

PIPES Install new Great 8 Open Diapason - 61 pipes
 Install modern tuning slides on all metal pipes
 Repack stoppers of all wood pipes.

ACTION CURRENT Install new 10-15 volt 15 ampere DC organ power unit with air-mercury switch.

BLOWER Present motor and blower to be used without change.

GENERAL The entire organ is to be returned to the factory of M. P. Moller, Inc. Hagerstown, Md. for rebuilding as specified above.

Cables

Supply new asbestos covered cables between console and organ. Cable length from (x) in console to (x) in organ - 15'-0".

114 St Marys Pl 2070

10/7 374

SPECIFICATIONS
OF
CONSOLE AND ORGAN

MANUAL COMPASS	CC to C4, 61 notes
PEDAL COMPASS	CCC to G, 32 notes
WIND PRESSURE	
PITCH	A-440 @ 70°F

GREAT ORGAN

1	8	Open Diapason.....new pipes, present action.....61 Pipes
2	8	Stopped Diapason...present pipes, present action.....61 Pipes
3	8	Dulciana.....present pipes, present action.....61 Pipes
4	4	Flute Traverso.....present pipes, present action.....61 Pipes

SWELL ORGAN

5	8	Gedeckt.....from #2.....61 Notes
6	8	Gamba TC.....present pipes, present action.....49 Pipes
7	8	Dolce.....from #3.....61 Notes
8	8	Vox Celeste TC....present pipes, present action.....49 Pipes
9	4	Flute.....from #4.....61 Notes
10		Tremolo

PEDAL ORGAN *

11	16	Bourdon.....present pipes, present action.....32 Pipes
----	----	--

(*) Pedal Organ playable thru slides in console

COUPLERS

12	Great to Pedal	19	Great 16
13	Great to Pedal 4	20	Great Unison Off
14	Swell to Pedal	21	Great 4
15	Swell to Pedal 4	22	Swell 16
16	Swell to Great 16	23	Swell Unison Off
17	Swell to Great	24	Swell 4
18	Swell to Great 4		

ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3
Pistons No. 1-2-3

Affecting Great and Pedal Stops
Affecting Swell and Pedal Stops

R-634

ST. MARY'S R. C. CHURCH, LAUREL, MARYLAND

SHEET 3

PEDAL MOVEMENTS

- 1 - Great to Pedal Reversible
- 2 - Balanced Expression Pedal (8 contacts, reverse system)
- 3 - Balanced Crescendo Pedal with indicator light (green jewel)

ACCESSORIES

Concave and radiating pedal keyboard
Organ bench with music shelf

Present motor and blower. New 15 ampere DC organ power unit with air-mercury switch.