

M. P. MÖLLER Organ Factory

3-25

Pipe Organ No. 9795 Date October 8, 1962
 For INDIANA CENTRAL COLLEGE, INDIANAPOLIS, INDIANA
 Action Moller's Electro-Pneumatic Console Detached
 Casing No. None * see sheet 3 Finish As Per Sample
 Decorations None Motor Swiss Blower No. 120-7 1:6 H.P.
Swiss Blower No. 120-5 1:1 H.P.
 Width of Key-bed Standard Stops and intra-manual couplers by draw
 Stop Controls knobs. Inter-manual couplers
 by tilting tablets.
 No. Manuals Three - Ivory Manual Keys Wind Pressure 3 1/2", Sw. 4 1/2", Pos. 2-3/4",
Ped. 3 1/2" & 4 1/2"
 To be Completed September 15, 1963 Blower Pipe furnished by Purchaser

SPECIFICATIONS

PITCH: A-440 @ 70°F

GENERAL: The organ is to be the distinctive work of M. P. Moller, Inc., not an assembled product. Quotation includes all freight and installation in the College.

GREAT ORGAN (Unenclosed) (Exposed Pipework) 7 3-1/2" Wind

1.	8°	Principal.....	46.....	17-1/2.....	12 Zinc S.M.....	61 Pipes
2.	8°	Spitzflöte.....	48-2/3.....	18-1/2.....	12 Zinc S.M.....	61 Pipes
3.	4°	Octave.....	58.....	18-1/2.....	S.M.....	61 Pipes
4.	IV Rks.	Fourniture.....	Formula "A"	18-1/2.....	S.M.....	244 Pipes
5.		Tremulant				

SWELL ORGAN 4-1/2" Wind

8

6.	8°	Gedeckt.....	54.....	20-1/2.....	12 Zinc S.M.....	61 Pipes
7.	8°	Gambe.....	52.....	18-1/2.....	12 Zinc S.M.....	61 Pipes
8.	8°	Gambe Celeste T.C.	54.....	18-1/2.....	S.M.....	49 Pipes
9.	4°	Nachthorn.....	56.....	18-1/2.....	S.M.....	61 Pipes
10.	2°	Blockflöte.....	68-3/4.....	20-1/2.....	S.M.....	61 Pipes
11.	II Rks.	Sesquialtera.....	Formula "B"	19-1/2.....	S.M.....	122 Pipes
12.	8°	Trompette.....	CC 3-1/2" T.C...	2-1/16".....	42-1/2.....	61 Pipes
13.		Tremulant				

POSITIV ORGAN (Unenclosed) (Exposed Pipework) 2-3/4" Wind

8

14.	8°	Copula.....	Reg. Stopped Bass & Treble.....	Wood.....	61 Pipes	
15.	4°	Rohrflöte.....	60.....	20-1/2.....	S.M.....	61 Pipes
16.	2°	Principal.....	70.....	17-1/2.....	S.M.....	61 Pipes
17.	1-1/3°	Superquint.....	80-2/3.....	18-1/2.....	S.M.....	61 Pipes
18.	III Rks.	Zimbel.....	Formula "C"	17-1/2.....	Tin.....	183 Pipes
19.	4°	Rohrschalmel.....	1-1/4".....			61 Pipes
20.		Tremulant				

PEDAL ORGAN 3-1/2" & 4-1/2" Wind

2

21.	16°	Subbass.....Large Ped. Bdn.....Wood..4-1/2" W.....32 Pipes
22.	16°	Rohrbourdon.....42...20-1/2...12 pipes 20 from #6..4-1/2" W.....32 Notes
23.	8°	Spitzprincipal.....45-3/4...17-1/2.....12 Zinc S.M...3-1/2" W..44 Pipes
24.	8°	Flauto Dolce.....from #6.....32 Notes
25.	4°	Spitzprincipal.....from #23.....32 Notes
26.	16°	Trompette...CCC 6"...CC 3-1/2"...12 pipes 20 from #12..4-1/2" W..32 Notes
27.	8°	Trompette.....from #12.....32 Notes
28.	4°	Trompette.....from #12.....32 Notes

COUPLERS

29.	Swell to Pedal
30.	Swell to Pedal 4°
31.	Great to Pedal
32.	Great to Pedal 4°
33.	Positiv to Pedal
34.	Swell to Great 16°
35.	Swell to Great
36.	Swell to Great 4°
37.	Positiv to Great 16°
38.	Positiv to Great
39.	Swell to Positiv 16°
40.	Swell to Positiv
41.	Swell to Positiv 4°
42.	Swell 16°
43.	Swell 4°
44.	Great 16°
45.	Great 4°
46.	Positiv 16°
47.	Swell Unison
48.	Great Unison
49.	Positiv Unison

ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3-4-5	Affecting Swell Organ
Pistons No. 1-2-3-4	Affecting Great Organ
Pistons No. 1-2-3-4	Affecting Positiv Organ
Toe Studs No. 1-2-3-4-5	Affecting Pedal Organ
Pistons No. 1-2-3-4-5-6	Affecting Full Organ
General Cancel Piston	

PEDAL MOVEMENTS

Swell to Pedal Reversible, duplicated by manual piston, affecting Swell to Pedal 4⁰ in OFF movement only.

Great to Pedal Reversible, duplicated by manual piston, affecting Great to Pedal 4⁰ in OFF movement only.

Positiv to Pedal Reversible, duplicated by manual piston.

Balanced Expression Pedal - Swell Organ.

Balanced Crescendo Pedal

Sforzando Pedal, duplicated by manual piston

ACCESSORIES

Crescendo indicator light, Green

Sforzando indicator light, Red

Action current indicator light, White

Radiating, concave pedal keyboard

Organ bench with music shelf

Light for music rack

Light for pedal claviver

Motor starter momentary contact switch installed in console

Electric motor, blower and action current power unit of ample capacity

Supply and install two (2) blower enclosures

GENERAL

M. P. Moller, Inc. to supply and install approximately 120 sq.ft. of panel work to cover the mechanism of the exposed Great and Positiv Organ.

* CASING

*Paneling to enclose exposed Great and Positiv Chestwork
and mechanism above platform floor level*

JHH/mb
11/30/62

MIXTURE FORMULASGREAT ORGANIV Rks. Fourniture Formula "A"

15	12	8	8
19	15	12	12
22	19	15	15
26	22	19	15
1-24	25-36	37-48	49-61

Unison 47 scale @ 8" CC 18-1/2 1/4 mouth S.M.
 Quint 48 scale @ 8" CC 18-1/2 1/4 mouth S.M.

SWELL ORGANII Rks. Sesquialtera Formula "B"

12	12
17	15
1-51	52-61

12th 66 scale 19-1/2 2/9 mouth S.M.
 15th 74 scale 19-1/2 2/9 mouth S.M.
 17th 75-1/3 scale 19-1/2 1/5 mouth S.M.

POSITIV ORGANIII Rks. Zimbel Formula "C"

29	26	22	19	15	12	8
33	29	26	22	19	15	12
36	33	29	26	22	19	15
1-12	13-24	25-36	37-42	43-48	49-54	55-61

Unison 50 scale @ 8" CC 17-1/2 1/4 mouth Tin
 Quint 52 scale @ 8" CC 17-1/2 1/4 mouth Tin