#### M. P. MOLLER ORGAN FACTORY

2/6

Pipe Organ No. R-1211	DateJune 18, 1990
For BEAVER CREEK CHRISTIAN C	HURCH, HAGERSTOWN, MARYLAND
Action <u>Electro-Pneumatic</u>	Console Present - Detached
Casing Present - no change	Finish Refinish same color
Decoration None	Motor45 HP Ventus 610812
Width of Key-bed <u>Standard</u>	Tracker Touch Yes No X
Keys to be Present Ivory	Stop ControlsTilting Tablets
No. ManualsTwo and Pedal	Wind Pressure 3 3/4"
To be Completed February 15, 1991	Blower Pipe Furnished by MPM, Inc.

#### **SPECIFICATIONS**

FOR

REBUILDING PRESENT MOLLER ORGAN
OPUS 4888 - 1927/R-469 - 1953 31228

CONSOLE

Reuse present console rebuilding as follows:

Install new nameboard with electric tilting tablets. Install new single memory solid state combination action.

Install new coupler system.

Replace all piston buttons and springs, adding new as required.

Replace crescendo and expression pedal pads and edging.

Replace burrs and felt washers on manual keys.

Refelt action as required.

Refelt pedal keyboard and install new insulating tips.

Recover roll top.

Repair and refinish console cabinet, bench and pedal keys.

Install new lights for music rack and pedal board.

OFFSET & UNIT

Recover the following actions and install new magnet armatures.

Great 8 Open Diapason - 12 notes

Install new actions as required.

CHIMES Reuse present bells and action without change.

R-1211 BEAVER	CREEK CHRISTIAN CHURCH, HAGERSTOWN, MARYLAND PAGE 2
SWITCHES	Install new solid state switches as required.
PEDAL ORGAN	Recover 32 note 16 Bourdon action and install new magnet armatures.
EXPRESSION	Install new swell shades and enclosure with electric action.
RESERVOIR	Install new reservoirs as required.
TREMOLO	Install new electro-pneumatic tremolo.
PIPES	Install new pipes as indicated by organ specifications.
	Revoice all pipes being reused. Repack all wood pipe stoppers. Install slide tuners as required.
CABLES	Install new plastic covered cables between console and organ.
	Install new action current wires between console, organ, and DC organ power unit.
ACTION CURRENT	<pre>Install new 11-15 volts, 35 amperes DC organ power unit.</pre>
BLOWER	Install new .45 HP, Ventus 610812 motor and blower.
GENERAL	All parts specified above to be rebuilt to be returned to the factory of M. P. Moller, Inc. at Hagerstown, Maryland.
	All parts from present instrument not required to complete this program become the property of M. P. Moller, Inc.
ų.	SPECIFICATIONS
	FOR CONSOLE AND ORGAN
MANUAL COMPASS PEDAL COMPASS WIND PRESSURE PITCH	CC to C4, 61 notes CCC to G, 32 notes 3 3/4" A-440 @ 70° F

R-1211 BEAVER CREEK CHRISTIAN CHURCH, HAGERSTOWN, MARYLAND PAGE 3

NEW PIPES AND ACTION UNLESS NOTED OTHERWISE

GREAT	ORGAN	-	Enclosed	with	Swell

Open Diapason...#1-61 present pipes; #1-12

-		present front pipe action92 pipes
2.	8	Rohrflötefrom #1161 notes
3.	8	Gemshornfrom #12
4.	4	Octave
5.	4	Waldflöte61 notes
6.	2	Super Octavefrom #161 notes
7.	1 1/3	Quint
8.	1	Cymbale
9.	8	Trompette
10.		Chimespresent bells, action, transformer,
September 19 set	3	relay and volume control21 bells
1		1
, ' —		

			SWELL ORGAN - Enclosed 4	
11. 12. 13. 14. 15. 16. 17.	2	8 8 8 4 2/3 2 8 4	Rohrflöte	pipes pipes notes notes notes pipes
19.			Tremulant	

## PEDAL ORGAN

20.	16	Bourdonpresent pipes and action32	pipes
21.	8	Rohrflötefrom #11	
22.	4	Principalfrom #1	notes

# COUPLERS

23.	Great	to	Pedal
24.	Swell	to	Pedal
25.	Swell	to	Great
26.	Swell	to	Great
27.	Swell	4	

1.

8

# ADJUSTABLE COMBINATIONS

Solid State - Single Memory

Pistons No. 1-2-3-4-5-6 Affecting Full Organ General Cancel Combination Adjustor Combination Lock

4

### PEDAL MOVEMENTS

Great to Pedal Reversible
Balanced Expression Pedal - Entire Organ
Balanced Crescendo Pedal with indicator lights

<u>ACCESSORIES</u> - Present unless noted

Concave, radiating pedal clavier
Organ bench with music shelf
Present music rack with new light
New Pedal light
Blower motor starter switch with indicator light
New DC organ power unit
New motor and blower

RVK/k 9/21/90