

M. P. MÖLLER Organ Factory

Pipe Organ No. 7776 Date November 17, 1948
 For TRINITY LUTHERAN CHURCH, RAPID CITY, SOUTH DAKOTA
 Action Electro-pneumatic Console Detached
 Casing No. None Finish As per sample
 Decorations None Motor 2 H.P., Style 3-P-3025
Stops & intra-man. coup. by drawknobs.
 Width of Key-bed Standard Stop Controls Inter-man. coup. by til-
ting tablets.
 No. Manuals Two Wind Pressure 4-1/2"
 To be Completed May 1, 1949 Blower Pipe furnished by Purchaser

PITCH A-440 SPECIFICATIONS

Great Organ

| | | |
|---|----|---|
| 1 | 8' | Diapason.....CC 40, TC 56..18-19- $\frac{1}{2}$..12 Zinc..S.M.....73 pipes |
| 2 | 8' | Harmonic Flute.....48.....12 Zinc..S.M.....85 pipes |
| 3 | 8' | Dulciana.....56.....12 Zinc..S.M.....73 pipes |
| 4 | 4' | Octave.....57.....18-19- $\frac{1}{2}$S.M.....73 pipes |
| 5 | 4' | Flute.....from #2.....73 notes |
| 6 | 2' | Fifteenth.....70.....S.M.....61 pipes |
| 7 | | Chimes.....(prepared for console only) |
| 8 | | Tremulant |

Swell Organ

| | | |
|----|--------|---|
| 9 | 16' | Rohrbourdon..(Unit).....42.....Capped...24 Zinc..S.M.....97 pipes |
| 10 | 8' | Rohrgedeckt.....from #9.....73 notes |
| 11 | 8' | Viole de Gambe.....54.....12 Zinc..S.M.....73 pipes |
| 12 | 8' | Viole Celeste..t.c.....56.....S.M.....61 pipes |
| 13 | 4' | Principal.....58.....S.M.....73 pipes |
| 14 | 4' | Rohrflöte.....from #9.....73 notes |
| 15 | 2-2/3' | Rohrnasat.....from #9.....61 notes |
| 16 | 2' | Flautino.....from #9.....61 notes |
| 17 | 8' | Trumpet.....4".....73 pipes |
| 18 | | Tremulant |
| 19 | | Blank |
| 20 | | Blank |

Pedal Organ

| | | |
|----|-----|--|
| 21 | 16' | Diapason.....CCC 30, CC 40.....12 pipes, 20 from #1.....32 notes |
| 22 | 16' | Bourdon.....Reg. Ped. Bdn.....44 pipes |
| 23 | 16' | Rohrbourdon.....from #9.....32 notes |
| 24 | 8' | Octave.....from #1.....32 notes |
| 25 | 8' | Bourdon.....from #22.....32 notes |
| 26 | 8' | Rohrflöte.....from #9.....32 notes |
| 27 | 4' | Super Octave.....from #1.....32 notes |
| 28 | 4' | Rohrflöte.....from #9.....32 notes |

Couplers

| | | | |
|----|--------------------|----|-----------|
| 29 | Great to Pedal | 36 | Great 16' |
| 30 | Great to Pedal 4' | 37 | Great 4' |
| 31 | Swell to Pedal | 38 | Swell 16' |
| 32 | Swell to Pedal 4' | 39 | Swell 4' |
| 33 | Swell to Great 16' | | |
| 34 | Swell to Great | | |
| 35 | Swell to Great | | |

Adjustable Combinations

| | |
|-----------------------|--------------------------------|
| Pistons No. 1-2-3-4 | Affecting Great Stops |
| Pistons No. 1-2-3-4 | Affecting Swell Stops |
| Pistons No. 1-2-3-4 | Affecting Pedal Stops |
| Pistons No. 1-2-3-4 | Generals, affecting full organ |
| General Cancel Piston | |

Pedal Movements

Great to Pedal Reversible
Balanced Expression Pedal - Great Organ
Balanced Expression Pedal - Swell Organ
Balanced Crescendo Pedal
Sforzando Pedal (duplicated by manual piston)
Swell to Pedal Reversible

Accessories

Crescendo Indicator Lights (4)
Sforzando Indicator Light
Concave, Radiating Pedal Clavier
Organ Bench with Music Shelf
Motor and blower (Steel Kinetic)
Action current generator
Console Lock

jr
1/4/49