

THE REUTER ORGAN COMPANY

LAWRENCE, KANSAS

PROPOSES A THREE MANUAL AND PEDAL PIPE ORGAN

(REVISED DESIGN) 3/45 existing RT Cons

FOR

FIRST PRESBYTERIAN CHURCH

CEDAR RAPIDS, IOWA

JUNE 17, 1970

Mr. Larry D. Krusie, District Representative  
236 West Cleveland, Freeport, Illinois 61032

THE *Reuter* ORGAN COMPANY

GENERAL SPECIFICATIONS

MANUALS	Compass CC to C4, 61 notes.
PEDAL	Compass CCC to G, 32 notes.
ACTION	Reuter's pitman, electro-pneumatic.
REGISTRATION	Controlled by drawknobs. The intramanual couplers are controlled by knobs placed with their respective stop groups, and the intermanual and manual to pedal couplers are controlled by tilting tablets placed above the top manual.
* CONSOLE	Detached.
PITCH	A-440.
CASEWORK	None except case for console.
ORGAN CHAMBERS	Suitable, finished chambers to be furnished by the purchaser.

\* Church's present console to be re-used. All couplers and pistons listed in the following specifications are those found on the present console. This proposal includes no renovation work of any sort on the console with the exception of changing the names of the drawknobs to the proper nomenclature.

GREAT ORGAN (Unenclosed)

<sup>12</sup>

- |     |                                    |                 |
|-----|------------------------------------|-----------------|
|     | <i>16' Violone</i>                 | <i>61 pipes</i> |
| 1.  | 16' Quintaton                      | 61 pipes.       |
| 2.  | 8' Principal                       | 61 pipes.       |
| 3.  | 8' Bourdon                         | 61 pipes.       |
| 4.  | 8' Erzähler                        | 61 pipes.       |
| 5.  | 4' Octave                          | 61 pipes.       |
| 6.  | 4' Koppelflöte                     | 61 pipes.       |
| 7.  | 2' Fifteenth                       | 61 pipes.       |
| 8.  | IV Mixture                         | 244 pipes.      |
| 9.  | <del>* 16' (Ch) Trumpet (TC)</del> |                 |
| 10. | * 8' (Ch) Trumpet                  |                 |
| 11. | * 4' (Ch) Trumpet                  |                 |

Chimes (Console Preparation)

Couplers to Great:

Great to Great 16'

Great Unison Off

Great to Great 4'

Swell to Great 16'

Swell to Great 8'

Swell to Great 4'

Choir-Positiv to Great 16'

Choir-Positiv to Great 8'

Choir-Positiv to Great 4'

\* These stops are not to be affected by any couplers.

SWELL ORGAN (Expressive) 14

12.	16' Rohrgedeckt	73 pipes.
13.	8' Rohrflöte	
14.	8' Viola	61 pipes.
15.	8' Viola Celeste (TC)	49 pipes.
16.	4' Spitzprincipal	61 pipes.
17.	4' Hohlflöte	61 pipes.
18.	2 2/3' Nasard	61 pipes.
19.	2' Blockflöte	61 pipes.
20.	1 3/5' Tierce	61 pipes.
21.	III Scharf	183 pipes.
22.	16' Fagotto (1/2 length)	85 pipes.
23.	8' Trompette	61 pipes.
24.	8' Fagotto <i>Clarion</i>	<i>61 pipes</i>
25.	4' Fagotto Clarion	

Tremolo

Couplers to Swell:

Swell to Swell 16'

Swell Unison Off

Swell to Swell 4'

Choir-Positiv to Swell 16'

Choir-Positiv to Swell 8'

Choir-Positiv to Swell 4'

CHOIR-POSITIV ORGAN (Expressive) <sup>10</sup>

26.	8' Gedeckt	61 pipes.
27.	8' Spitzflöte	61 pipes.
28.	8' Spitzflöte Celeste (TC)	49 pipes.
29.	4' Nachthorn	61 pipes.
30.	2' Principal	61 pipes.
31.	1 1/3' Larigot	61 pipes.
32.	II Zimbel	122 pipes.
33.	8' Trumpet	61 pipes.
34.	8' Krummhorn	61 pipes.

Tremolo

Couplers to Choir-Positiv:

Choir-Positiv to Choir-Positiv 16'

Choir-Positiv Unison Off

Choir-Positiv to Choir-Positiv 4'

Swell to Choir-Positiv 16'

Swell to Choir-Positiv 8'

Swell to Choir-Positiv 4'

- |     |                           |           |
|-----|---------------------------|-----------|
| 35. | 32' Resultant             |           |
| 36. | 16' Principal             | 32 pipes. |
|     | 16' <i>(Det) Violone</i>  |           |
| 37. | 16' Bourdon               | 56 pipes. |
| 38. | 16' (Gt) Quintaton        |           |
| 39. | 16' (Sw) Rohrgedeckt      |           |
| 40. | 8' Octave                 | 32 pipes. |
| 41. | 8' Bourdon                |           |
| 42. | 8' (Sw) Rohrfloöte        |           |
| 43. | 4' Choral Bass            | 32 pipes. |
| 44. | 4' Bourdon                |           |
| 45. | 2' Waldfloöte             | 32 pipes. |
| 46. | III Mixture               | 96 pipes. |
| 47. | 16' Posaune               | 56 pipes. |
| 48. | 16' (Sw) Fagotto          |           |
| 49. | 8' Posaune                |           |
| 50. | 4' Clarion (from Posaune) |           |

Couplers to Pedal:

Great to Pedal 8'

Great to Pedal 4'

Swell to Pedal 8'

Swell to Pedal 4'

Choir-Positiv to Pedal 8'

Choir-Positiv to Pedal 4'

### ADJUSTABLE COMBINATIONS

Operated by pistons under their respective manuals.  
Adjustable at keyboard and visibly affecting the stop controls.

Eight, thumb pistons affecting the Great stops and intramanual couplers.

Eight, thumb pistons affecting the Swell stops and intramanual couplers.

Eight, thumb pistons affecting the Choir-Positiv stops and intramanual couplers.

Eight, toe pistons affecting the Pedal stops only.

Three, toe pistons affecting the intermanual and manual to pedal couplers only.

Six, thumb pistons acting on all stops and couplers of the entire organ,  
duplicated on toe pistons.

General Cancel thumb piston.

### COMBINATION COUPLERS

Pedal combinations to Great pistons, on and off.

Pedal combinations to Swell pistons, on and off.

Pedal combinations to Choir-Positiv pistons, on and off.

### REVERSIBLES

Great to Pedal, toe piston.

Swell to Pedal, toe piston.

Choir-Positiv to Pedal, toe piston.

Full Organ, duplicate thumb and toe pistons.

### PEDAL MOVEMENTS

Register Crescendo Pedal.

Balanced Expression Pedal, Swell Organ.

Balanced Expression Pedal, Choir-Positiv Organ.

NOTE: All controls listed on this page are presently in the church's existing Reuter console.

\* ACCESSORIES

Current Indicator Light.

Crescendo Indicator Light.

Full Organ Indicator Light.

Music rack with fluorescent light at base.

Organist's bench with blocks for height adjustment.

A. G. O. standard pedal keyboard.

\*\* Organ blower and motor of ample capacity.

\*\* Action current power unit.

Static reservoir on blower.

Pedal board light.

\* All console accessories listed on this page are presently in the church's existing Reuter console.

\*\* The church's present blower and action current power unit are to be re-used. A new static pressure control reservoir will be provided.

Standard details of construction (8/67) a part of this contract.