# M. P. MÖLLER Organ Factory

2

Pipe Organ No.	R=609	Date	July 19, 1957
	TRINITY METHODIST CHURC		
Action	Electro-Pneumatic	Console	Present
Casing No.	especial appeals and a surface of the surface of th	Finish _	
Decorations		Motor_	Present
Width of Key-bed		Stop Cor	atrols Draw-Knobs & Tilting Tablets
No. Manuals			essure No Change
To be Completed_	October 1, 1958	Blower 1	Pipe furnished by No Change

### SPECIFICATIONS

FOR

REPAIRS TO MOLLER ORGANS OPUS 6070 & 6071 - 1933

## MAIN ORGAN OPUS 6070

#### CONSOLE

Adjust and regulate entire combination action.

Adjust all contacts for 1st and 2nd touch on all pistons.

Replace bumper felt in pedal keyboard.

Replace rubber tips on pedal keys.

Replace felt bushings in pedal key guides.

Vacuum clean entire console.

### GREAT ORGAN

Releather two 73 note primary stations.
Releather and rework one 73 note contact box.
Releather eight 73 note electro-pneumatic switches.
Replace 319 outside magnet armatures.
Recover 56 shade and bumper pneumatics.
Refit and Lubricate all expression shades.
Recover two shade reservoirs 1°-2" x 1°-8".
Clean and wipe all labial pipes.
Clean and polish tongues and eschallots in reed pipes.
Vacuum clean entire organ.
Tone regulate and tune organ.

#### SWELL ORGAN

Releather four 73 note primary stations.
Releather and rework one contact box.
Releather three 73 note electro-pneumatic switches.
Releather five 12 note electro-pneumatic switches.
Releather 393 outside magnet armatures.
Recover 22 shade and bumper pneumatics.
Recover one shade reservoir 1°-2" x 1°-8"
Refit and Lubricate all expression shades.
Clean and wipe all labial pipes.
Clean and polish tongues and eschallots in reed pipes.
Vacuum clean entire organ.
Tone regulate and tune organ.

#### CHOIR ORGAN

Releather two 73 note primary stations.
Releather ten 73 note electro-pneumatic switches.
Releather one 25 note electro-pneumatic switch.
Releather and rework one 73 note contact box.
Replace 316 cutside magnet armatures.
Recover 16 shade and bumper pneumatics.
Refit and Lubricate all expression shades.
Recover one shade reservoir 1°-2° x 1°-8°
Clean and wipe all labial pipes.
Clean and polish tongues and eschallots in reed pipes.
Vacuum clean entire organ.
Tone regulate and tune organ.

#### SOLO ORGAN

Releather three 73 note primary stations.
Releather eight 73 note electro-pneumatic switches.
Releather three 12 note electro-pneumatic switches.
Releather and rework one 73 note contact box.
Replace 271 outside magnet armatures.
Recover 16 shade and bumper pneumatics.
Recover two shade reservoirs 1°-2° x 1°-8°.
Refit and Lubricate all expression shades.
Clean and wipe all labial pipes.
Clean and polish tongues and eschallots in reed pipes.
Vacuum clean entire organ.
Tone regulate and tune organ.

#### ECHO ORGAN

Releather two 73 note primary stations.
Releather eighteen 73 note electro-paeumatic switches.
Releather four 25 note electro-paeumatic switches.
Releather and rework two 73 note contact boxes.
Replace 483 outside magnet armatures.
Recover 8 shade and bumper paeumatics.
Recover one shade winker paeumatics.
Recover 25 Chime striker paeumatics.
Recover 25 Chime damper paeumatics.
Refit and Lubricate all expression shades.
Releather one 3°=0° x 3°=0° Echo blower reservoir.
Clean and wipe all labial pipes.
Clean and polish tongues and eschallots in reed pipes.
Vacuum clean entire organ.
Tone regulate and tune organ.

#### PEDAL ORGAN

Releather nineteen 32 note electro-pneumatic switches. Replace 151 outside magnet armatures. Clean and wipe all labial pipes. Clean and polish tongues and eschallots in reed pipes. Vacuum clean entire organ. Tone regulate and tune organ.

### CHAPEL ORGAN OPUS 6071

#### CONSOLE

Adjust drawknobs, combination fiber togles and jacks. Replace bumper felt in pedal keyboard. Replace rubber tips on pedal keys. Replace felt bushings in pedal key guides. Vacuum clean entire console.

#### ORGAN CHAMBER

Releather two 73 note primary stations.
Releather seven 73 note electro-pneumatic switches.
Releather four 12 note electro-pneumatic switches.
Releather and rework two 73 note contact boxes.
Replace 313 outside magnet armatures.
Recover 18 shade and bumper pneumatics.
Refit and Lubricate all expression shades.
Recover one shade reservoir 1°-2° x 1°-8°.
Clean and wipe all labial pipes.
Clean and polish tongues and eschallots in reed pipes.
Vacuum clean entire organ.
Tone regulate and tune organ.