M. P. MÖLLER Organ Factory

File

	Official Particular State Control of Control	Resident Control of the Control of t	
Pipe Organ No	R-665	Date	
For an annual and a second	GRACE UNITED CHURCH OF CHRIST (	EDEN) LANCASTER, PA.	
Action	Electro-Pneumatic	Console Present Attached - No Change	
Casing No.	Present - No Change	Finish No Change	
Decorations	Present - No Change	Motor Present Motor, Blower & DC Organ F	Power
Width of Key-bed.	No Change	Stop Controls Present - No Change Ur	nit
No. Manuals		Wind Pressure 3"	
To be Completed_		Blower Pipe furnished by Present	
	SPECIFICAT	IONS	
	FOR		
	REBUILDING PRESENT MOLLER ORG	HAN OPUS 5642 - 1929	
CONSOLE	Rebuild the existing console me	echanism as follows:	
	Install new silver contacts on Install 9 new coupler slides wi Install new combination action Install 11 new coupler pneumati	th silver contacts	

Install new 13 note primary station with coupler slides

Install new expression pedal with new roller switch with silver contacts

Install new crescendo pedal with new roller switch with silver contacts

Install new Great to Pedal Reversible

Refelt console completely Clean and polish console case Refelt pedal keyboard completely Clean and refinish pedal keyboard

MANUAL CHEST

Releather 295 manual pipe pouches
Install 549 new stop action checks and eyelets
Install 244 new duplex shifters
Releather two 61 note primary stations
Releather one 9 note stop action primary
Install 131 new magnet armatures

CONTACT BOX

CHIMES

OFFSET ACTION Releather Great 8 Open Diapason action #1 to #10 incl. and install new magnet armatures.

Install new 10 note single finger contact box for Great 8 Open Diapason #1 to #10 incl.

Install one set Deagan Class D-21 Tube Chimes complete with electro pneumatic action.

PEDAL ORGAN Releather 16 Bourdon action #1 to #32 incl. and install new magnet armatures.

EXPRESSION Present expression action to be used without change.

R-665	GRACE UNITED CHURCH OF CHRIST, (EDEN), LANCASTER, PA.	
RESERVOIRS	Releather one 2°-0" x 4°-0" Manual reservoir Releather two 16" x 21" Pedal reservoirs Releather one 2°-6" x 2°-6" Blower reservoir	
TREMOLO	Install one new electro-pneumatic tremolo	
PIPES	Tune and tone-regulate organ	
CABLES	Present cables between console and organ to be used without change.	
BLOWER	Present motor and blower to be used wit hout change.	
ACTION CURRENT	Present DC organ power unit to be used without change.	
GENERAL	Parts specified for rework to be returned to factory of M. P. Moller, Inc. at Hagerstown, Maryland for rebuilding as specified above.	
	* * * * * * * * * * * * * * * * * * * *	
	SPECIFICATIONS OF CONSOLE AND ORGAN	
MANUAL COMPASS PEDAL COMPASS WIND PRESSURE PITCH	CC to Ch, 61 notes CCC to G, 32 notes A-hho @ 70 F	
	GREAT ORGAN	
1 8 8 8 8 8 4 8 5 4	Open Diapasonpresent pipes & action	
	SWELL ORGAN	
7 8 8 8 9 8 10 4	Stopped Diapasonfrom #2	
PEDAL ORGAN *		
12 16 13 16	Bourdon	

(\*) Pedal Organ playable thru slides in console

## COUPLERS

14	Great to Pedal
15	Swell to Pedal
16	Swell to Great 16
17	Swell to Great
18	Swell to Great 4
19	Great 16
20	Great h
21	Swell 16
22	Swell h

## ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3 Pistons No. 1-2-3 Affecting Great and Pedal stops Affecting Swell and Pedal stops

## PEDAL MOVEMENTS

- 1 Great to Pedal Reversible
- 2 Balanced Expression Pedal \* present mechanical action )
- 3 Balanced Crescendo Pedal with indicator light (green jewel)

Number of contacts and type of system to be same as present switch)

## ACCESS ORTES

Present concave and radiating pedal keyboard Present organ bench with music shelf

Present motor, blower and DC organ power unit.