

M. P. MÖLLER Organ Factory

Pipe Organ No. 7874 Date April 30, 1948
 For NED. HERV. KERK, WITBANK, TRANSVAAL, SOUTH AFRICA
 Action Electro-pneumatic Console Detached All Electric
 Casing No. 15 Display pipes, Gilded, 3 Trisets Finish Mahogany to Match Kejaht
 Decorations None Motor Blower & Generator by Purchaser
 Width of Key-bed Standard Stop Controls Stop Keys
 No. Manuals Two Wind Pressure 6"
 To be Completed Soon as possible Blower Pipe furnished by Moller
 Altitude 5,300 ft.

PITCH A-440 SPECIFICATIONS

Great Organ

1	8'	Open Diapason (Unenclosed)	42.....17 Zinc C.M.	73 73 pipes
2	8'	Stopped Diapason.....	from #7.....	73 pipes
3	8'	Dulciana.....	56.....12 Zinc S.M.....	85 pipes
4	4'	Liebligh Flute.....	from #7.....	73 notes
5	4'	Dulcet.....	from #3.....	73 notes
6	8'	Cornopean.....	from #14.....	73 notes

Swell Organ

7	16'	Liebligh Bourdon (Unit)..	Reg. Man. Bdn.....	97 pipes
8	8'	Stopped Flute.....	from #7.....	73 notes
9	8'	Gamba.....	54.....12 Zinc S.M.....	85 pipes
10	4'	Flute.....	from #7.....	73 notes
11	4'	Gambette.....	from #9.....	73 notes
12	2-2/3'	Nazard.....	from #7.....	61 notes
13	2'	Flautino.....	from #7.....	61 notes
14	8'	Cornopean.....	4-1/2.....	73 pipes
15		Tremulant		

Pedal Organ

16	16'	Bourdon..(Unenclosed)....	Reg. Ped. Bdn.....	44 pipes
17	16'	Liebligh Bourdon.....	from #7.....	32 notes
18	8'	Bass Flute.....	from #16.....	32 12 pipes
19	4'	Flute.....	from #7.....	32 notes

Couplers

20	<u>Swell</u> to Great	26	Great to Pedal
21	Swell Octave	27	Swell Sub Octave to Great
22	Great Sub Octave	28	Great Octave
23	Swell Octave to Pedal	29	Swell to Pedal
24	Swell Octave to Great		
25	Swell Sub Octave		

Adjustable Combinations

Pistons No. 1-2-3 Affecting Great and Pedal Stops
Pistons No. 1-2-3 Affecting Swell and Pedal Stops

Pedal Movements

Great to Pedal Reversible
Balanced Swell Pedal
Balanced Crescendo Pedal

Accessories

Crescendo Indicator
Organist's Bench with music shelf
Concave Radiating Pedal Clavier

General

Console This is located on the gallery opposite the organ, length of cable is marked. This goes across the ceiling. Please send suitable saddles for main cables. Furnished in Mahogany to match Kejaat. If main cable could enter under pedals it would save casing in.

Supply push button switch in Console.

Display Pipes Three groups by M. P. Moller. A grille is already installed in 3 sections as shown. We require 15 display pipes located in 3 trisets. These could be fitted by you with pipe loops stays etc. The pipe blocks and stays which will be seen must be furnished in teak (oiled only) to match present Grille.

Pipes to be gilded.

No blower or generator.

No swell box

No display case.

Supply enough main conductor to reach blower. Send usual spares. Witbank is a Colliery town 100 miles from Johannesburg. The altitude is 5,300 feet.

Address to

Cooper, Gill & Tomkins (pty) Ltd.,
Ned. Herv. Kerk.
Witbank,
Transvaal, South Africa

SHIP VIA DURBAN