M. P. MÖLLER Organ Factory

10855 March 25, 1972 Pipe Organ No .. Thata NORWAY LUTHERAN CHURCH, WIND LAKE, WISCONSIN For Moller's Pitman Electro-Pneumaticale Detached. Without roll top Action None As Per Sample Winish Casing No_ None Motor Meidinger Decorations . Tablet Type Standard Stop Controls Width of Key-bed TWO Heavyout English Ivory Kewand Pressure 2-3/4" No. Manuals To be Completed November 15, 1972 Blower Pipe furnished by Purchaser SPECIFICATIONS PITCH: A-440 The organ shall be a distinctive work of the builder, a custom GENERAL: product of his factory, in no way a stock instrument nor assembled from outside parts. GREAT ORGAN (unenclosed and exposed) 10 8' 2. Spitzflote......48-2/3...18-1/2......12 Zinc S.M....61 pipes 81 3. 4 . 2 9 4. 5. Chines. (present bells and action) A to P #22 to #22 bells

Chines. (present bells and action) A to P #22 to #22 bells

Present beggin (lass & "tubes + action A-#22 to t-442 in

Supply action relays, 5 stage transformer + wolume routed switch wolume control

Supply action relays, 5 stage transformer + wolume routed switch wolume sontiol

2 trubes 6. 81 Rohrflöte.....54.....21-1/2.....12 Zinc S.M....61 pipes 7. 8 Salicional (tapered)...52-3/4...17-1/2......12 Zinc S.M....61 pipes 8. 40 9. 21 10. 11. II Rks. 12 81 13. Tremolo 4 PEDAL ORGAN (unenclosed and exposed) 14. 16 88 15. 16. 4 9 17. 16 Fagotto.....3-3/4"..1-44 half length Tpt. Patt.....56 pipes 4 ? 18. COUPLERS 19. Great to Pedal 8' 24. Swell to Pedal 8' Swell to Great 16' 25. Swell to Pedal 4' 20. Swell 16' 21. Swell to Great 8' 26. 22. Swell to Great 4' 27. Swell 4' 23. Great 4'

ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3-4-5-6-7-8

General, affecting entire organ, beneath Swell Center

ACCESSORIES

Crescendo pedal for entire organ, with indicator light, Chimes-Tremolo cut-out switch.

Great to Pedal Reversible piston, duplicated to pedal.

Swell to Pedal Reversible piston, duplicated to pedal. Affects Swell to Pedal 4 coupler in off movement

Swell expression pedal

Swell box partitions and shade actions as required. Shades to have 900 opening, tandem operation.

Solid wood music rack with Castlelight. Light for pedal board.

Concave, radiating pedal clavier.

Circuit breakers for organ action protection, 15 ampere maximum per circuit.

Organ beach with music shelf

Electric motor, silent Meidinger blower with sound proofed enclosure, static reservoir, as required.

Action current rectifier, as required

Lockswitch for motor to be mounted in console

All wind conduits to connect the various parts to be included as required.

GENERAL

The organ shall be assembled and tested at the factory, then delivered, installed and finished (receive final voicing) in the Church by Moller staff. The organ shall be presented ready for use.

Cabinetry to enclose the exposed mechanisms and chests is not included, though is available if desired, on separate order following completion of the engineering lavout.

JHH/mr 4/20/72

Salesman: Henry Beard

ORGAN NO. 10855 NORWAY LUTHERAN CHURCH, WIND LAKE, WISCONSIN

MIXTURE FORMULAS

GREAT ORGAN III Rks. Mixture Formula "A"

1-12	13-24	25-42	43-54	15 55-61
29	26	22	10	
26	22	19	15	12
22	19	15	12	8

Unison 48 @ 8' CC 17-1/2 1/4 mouth S.M. Quint 49 @ 8' CC 17-1/2 2/9 mouth S.M.

SWELL ORGAN II Rks. Cymbel Formula "B"

29		26	22	19	15	8
33		29	26	22	19	12
1-18		19-36	37-42	43-49	50-56	57-61
lini eon	AR	@ 21 CC	17_1/9	7 /A mandh	C BA	

49 @ 8' CC 17-1/2 2/9 mouth S.M. Quint