

M. P. MÖLLER Organ Factory

File

Pipe Organ No.	7774	Date	November 11, 1947
For	DUTCH REFORMED CHURCH, BENONI, TRANSVAAL, SOUTH AFRICA		
Action	Electro-pneumatic	Console	Detached
Casing No.	Case & Display Pipes	Finish	As per sample
Decorations	None	Motor & Generator by Purchaser	
Width of Key-bed	Standard	Stop Controls	Stop Keys
No. Manuals	Two	Wind Pressure	6"
To be Completed	Soon as possible	Blower Pipe furnished by <u>Moller</u>	

SPECIFICATIONS

PITCH: A-440

Great Organ

1	8'	Major Diapason....(Unenclosed)....42....12 Zinc....S.M.....85 pipes
2	8'	Geigen Diapason.....45.....12 Zinc....S.M.....73 pipes
3	8'	Stopped Flute.....from #9.....73 notes
4	8'	Dulciana.....56.....12 Zinc....S.M.....85 pipes
5	4'	Principal.....from #1.....73 notes
6	4'	Lieblighflöte.....from #9.....73 notes
7	4'	Dulciana.....from #4.....73 notes
8	8'	Horn.....from #18.....73 notes

Swell Organ

9	16'	Lieblighbourdon (Unit).....Reg. Man. Bdn.....97 pipes
10	8'	Geigen Diapason.....from #2.....73 notes
11	8'	Stopped Flute.....from #9.....73 notes
12	8'	Gamba.....56.....12 Zinc....S.M.....85 pipes
13	4'	Lieblighflöte.....from #9.....73 notes
14	4'	Gambette.....from #12.....73 notes
15	2-2/3'	Nazard.....from #9.....61 notes
16	2	Flautino.....from #9.....61 notes
17	8'	Oboe.....(Prepared for console only)
18	8'	Horn.....4".....73 pipes
19		Tremolo

Pedal Organ

20	16'	Bourdon.....(Unenclosed).....Reg. Ped. Bdn.....44 pipes
21	16'	Liebligh Bourdon.....from #9.....32 notes
22	8'	Bourdon.....from #20.....32 notes
23	4'	Stopped Flute.....from #9.....32 notes
24	16'	Trombone.....(prepared for console only)

Stop Keys 1, 5, 20 & 22 to be engraved in red.

Couplers

25	Great to Pedal	30	Swell 16'
26	Great 16'	31	Swell 4'
27	Great 4'	32	Swell to Great 16'
28	Swell to Pedal	33	Swell to Great 8'
29	Swell to Pedal 4'	34	Swell to Great 4'

Adjustable Combinations

Pistons No. 1-2-3.	Affecting Great and Pedal Stops
Pistons No. 1-2-3	Affecting Swell and Pedal Stops

Pedal Movements

Great to Pedal Reversible
 Balanced Expression Pedal
 Balanced Crescendo Pedal

Accessories

Crescendo Indicator Light
 Radiating, Concave Pedal Clavier
 Organ Bench with Music Shelf
 Silent motor, starter push button switch

General

CASE	The Church is Norman in design of Architecture. The bottom panel work or pipe toes should not exceed 6 feet 6 inches in height from the floor. In the small front, the panel work could be left out where it comes against the gallery front. This should be furnished in oak and coloured the same shade as the Console you supplied at Yeoville, St. Mark's. Send filits to fit to wall same lumber as case. Please forward design of case when completed.
CONSOLE	This to be of your Standard design, electro-pneumatic. Fit push button switch in Bass side of Key-board.
SWELL BOX	If this is built in the corner no back or end is required, but send suitable lumber to plug to wall to take top and front. Vertical shade to be installed.
BLOWER	No blower or generator to be supplied but send suitable Blower Conductor and Blower Reservoir. 16 feet straight conductor is required below floor level.

ADDRESS CASES TO

Cooper, Gill & Tomkins, (Pty.) Ltd.
Dutch Reformed Church
Cranbourne Avenue
BENONI. Transvaal, S.A.

AND SHIP VIA DURBAN

JHHjr
4/20/48