M. P. MÖLLER Organ Factory

	A V AD V EX V A V AN THE CONTRACTOR AND CONTRACTOR	otapoven.	
Pipe Organ No	M-2360	Date April 1,	1967 Rev'd 11/17/67
For	FIRST METHODIST CHURCH, BURLIN	GAME, CALIFORNIA	
Action	Electro-Pneumatic	_ConsolePresc	ent
Casing No	None	Finish Pres	ent
Decorations	Display Pepes by M.P.M. In	Motor for Gr-Ped	organ. New DC organ power
Width of Key-bed_	Standard O	Stop Controls	Draw knobs & Tilting Tablet
No. Manuals	Three and Pedal	_Wind Pressure	
To be Completed_	March 1, 1968	Blower Pipe furnis	hed by Purchaser
	SPECIFICAT		
	FOR		
	CHANGES AND ADDITIONS TO EXIST	TING ESTEY ORGAN	
CREAT ORGAN	Install new unenclosed and exp division complete, in space to Supply necessary replacement	be supplied by cu	t Organ stomer.
SWEIL ORGAN	Install present Great 8 Diapas Diapason action to play as h l replacement draw knobs.	son pipes on presen Principal. Supply	t Swell 8 necessary
CHOIR ORGAN	Install new 8 Unda Maris pipes Install new 8 Krummhorn pipes Install new 89 note unit actic Supply necessary replacement	on present Great 8 on for 8 Gemshorn.	Diapason action.
PEDAL ORGAN	Install the following new uner with new unenclosed and expose	nclosed and exposed ed Great Organ divi	Pedal stops sions:
The state of the s	16 Principal - 12 Pipe 16 Bassoon - bl Pipe		
SWITCHES	Supply necessary replacement new 6/ note thou Install, the following ele on and wired to relay Choir 8 Gemshorn - 61 Choir 2-2/3 Twelfth - Choir 2 Fifteenth - 6	Notes - # 20 X	incl 73 incl 6 #80 incl 4 85 incl
EXPRESS ION	Unoir 1-3/5 Herce -	tation Cut Cut - 63 - 19 Notes - # 1 To # 1 to # 61 incl - itional shades only action. itional shades only	Hotes 449 incl 61 notes 10tes in Swell Organ

#M-2360

FIRST METHODIST CHURCH, BURLINGAME, CALIFORNIA

Page 2

RESERVOIRS

Install new 3'-0" x 3'-0" blower reservoir, complete with springs and rails for present blower.

Install new blower reservoir as required for new blower.

Install new main and offset reservoirs as required for Great and Pedal Organ additions.

Install new reservoir as required for new Choir 8 Gemshorn unit action.

Install concussions on new main chests.

TREMOLO

Install one new electro-pneumatic tremolo in Choir Organ.

PIPES

Supply the following new pipes:

Great	o Principal		CT	Pipes
Great	8 Bourdon		61	Pipes
Great	4 Octave		61	Pipes
Great	4 Rohrflöte		61	Pipes
Great	2 Waldflöte		61	Pipes
Great	III Mixture			Pipes
Choir	8 Gemshorn		89	Pipes
Choir	8 Unda Maris	TC	49	Pipes
Choir	8 Krummhorn		61	Pipes
Pedal	16 Principal		12	Pipes
Pedal	16 Bassoon		ble	Pipes

Revoice Choir 8 Tuba Bombarde (present Great 8 Harmonic Tuba pipes)

CABLES

Install new plastic covered cables as required.

Install new action current wires as required.

BLOWER

Install new motor and blower for new Great Organ.

Present motor and blower to be used without change for balance of organ.

ACTION CURRENT

Install new DC organ power unit of ample capacity.

SPECIFICATIONS

FOR

CONSOLE AND ORGAN

MANUAL COMPASS
PEDAL COMPASS
WIND PRESSURE
PITCH

CC to Ch, 61 Notes CCC to G, 32 Notes 6" A-hh0 @ 70° F

35

		GREAT ORGAN (unenclosed & exposed)
12345678	16 8 8 4 4 2 III	Violone
	· ·	SWELL ORGAN (no change except as noted)
9 10 11 12 13 14 15 16 17 18 19 20 21 22	16 8 8 8 4 14 2 IV 16 8 8	Bourdon Gedeckt Salicional Voix Celeste Principalpresent Great 8 Diapason pipes; present Swell 8 Diapason action Flute Piccolo Mixture Trompette Trompette Oboe Vox Humana Clarion Tremulant
		CHOIR ORGAN (no change except as noted)
23 24 25 26 27 28 29 30 31 32 33 * 34	8 8 8 8 8 4 2-2/3 1-3/5 8	Viole Concert Flute Gemshorn (unit)new pipes; new action

^(*) Choir 16 coupler draw knob to be used for this stop control.

Tremulant.....new

Page 4	P	a	ge	4
--------	---	---	----	---

#M-2360

FIRST METHODIST CHURCH, BURLINGAME, CALIFORNIA

PEDAL ORGAN (no change except as noted)

36	16	Diapason
37	*16	Principal12 new pipes, new action; 20 from #232 Notes
38	16	Contra Bass
39	16	Bourdon
40	16	Gedeckt
41	8	Flute
42	8	Cello
42 43 44	4	Flute
14	*16	Bassoonhew pipes; new action
1.5	8	Ressort #101

(*) unenclosed and exposed

COUPLERS

No Change except deletion of Choir 16 coupler which is to be used for Choir 8 Tuba Bombarde control.

Supply on-off jamb switch for Choir 16.

ADJUSTABLE COMBINATIONS

No Change

No Change

PEDAL MOVEMENTS

No Change

No Change

ACCESSORIES (no change except as noted)

Present motor and blower for Swell & Choir organs.

New motor and blower for Great Organ.

New DC organ power unit of ample capacity.