

#172

THE REUTER ORGAN COMPANY

LAWRENCE, KANSAS

PROPOSES A TWO MANUAL PIPE ORGAN

(REVISED SPECIFICATION)

2/21

FOR

FIRST CONGREGATIONAL CHURCH

LITCHFIELD, CONNECTICUT

MARCH 21, 1969

Mr. Barclay Wood, District Representative
38 Cedar Street, Worcester, Massachusetts 01609

THE *Reuter* ORGAN COMPANY

21560
U S

GENERAL SPECIFICATIONS

MANUALS

Compass CC to C4, 61 notes.
English Ivory Keys.
Reuter "Tracker Touch".

PEDAL

Compass CCC to G, 32 notes.

ACTION

Reuter's pitman, electro-pneumatic.

REGISTRATION

Controlled by draw knobs. The intra-manual couplers are controlled by knobs placed with their respective stop group and the intermanual and manual-to-pedal couplers are controlled by tilting tabl placed above the top manual.

CONSOLE

Detached.

PITCH

A-440.

CASEWORK

None except case for console. Such casework as may be desired to enclose the mechanical portions of the exposed pipework to be furnished by the purchaser.

ORGAN CHAMBER

Suitable, finished chamber to be furnished by the purchaser. The existing organ case is to be reused with minor modifications to serve as the chamber for the new organ. Note that portions of the exposed Great division for the new organ will project approximately 2' in front of the present case

EXPRESSION ENCLOSURE

An expression enclosure to house the expressive portion of the organ to be provided by The Reuter Organ Company.

GREAT ORGAN (Exposed) 7

- | | | | |
|----|--------|-----------------|------------|
| 1. | 8' | Principal | 61 pipes. |
| 2. | ✓ * 8' | Spitzflöte | 61 pipes. |
| 3. | 4' | Octave | 61 pipes. |
| 4. | 4' | (Sw) Rohrfloöte | |
| 5. | 2' | Fifteenth | 61 pipes. |
| 6. | III | Mixture | 183 pipes. |

Chimes (Console Preparation)

Couplers to Great:

- ✓ Great to Great 16'
- ✓ Great Unison Off
- ✓ Great to Great 4'
- ✓ Swell to Great 16'
- ✓ Swell to Great 8'
- ✓ Swell to Great 4'

* This stop is to be located within the expression enclosure, along with the Swell division, thus permitting it to be affected by the Swell expression.

7.	✓ 16'	Rohrflöte	¹³ 85 pipes.
8.	8'	Rohrflöte	
9.	8'	Viole de Gambe	61 pipes.
10.	8'	Viole Celeste (TC)	49 pipes.
11.	4'	Principal	61 pipes.
12.	4'	Koppelflöte	61 pipes.
13.	✓ 2 2/3'	Nasard	61 pipes.
14.	✓ 2'	Blockflöte	61 pipes.
15.	1 3/5'	Tierce	61 pipes.
16.	II	Mixture	122 pipes.
17.	16'	Fagotto	85 pipes.
18.	8'	Trompette	61 pipes.
19.	✓ 4'	Clarion Fagotto	

Tremolo

Couplers to Swell:

✓ Swell to Swell 16'

✓ Swell Unison Off

✓ Swell to Swell 4'

- | | | | |
|-----|-----|------------------|-----------|
| 20. | 16' | Subbass | 32 pipes. |
| 21. | 16' | (Sw) Rohrgedeckt | |
| 22. | 8' | Octave | 44 pipes. |
| 23. | 8' | (Sw) Rohrflöte | |
| 24. | 4' | Super Octave | |
| 25. | 4' | (Sw) Rohrflöte | |
| 26. | 16' | (Sw) Fagotto | |
| 27. | 8' | (Sw) Fagotto | |
| 28. | 4' | (Sw) Fagotto | |

Couplers to Pedal:

- ✓ Great to Pedal 8'
- ✓ Great to Pedal 4'
- ✓ Swell to Pedal 8'
- ✓ Swell to Pedal 4'

ADJUSTABLE COMBINATIONS

Operated by pistons under their respective manuals. Adjustable at keyboard and visibly affecting stop controls.

Four, thumb pistons affecting the Great and Pedal Organs and their couplers.

Four, thumb pistons affecting the Swell and Pedal Organs and their couplers.

Four, thumb pistons acting on all stops and couplers of the entire organ.

General Cancel, thumb piston.

PEDAL MOVEMENTS

Register Crescendo Pedal.

Balanced Expression Pedal, Swell Organ.

REVERSIBLES

Great to Pedal, toe piston.

Full Organ, thumb and toe pistons.

ACCESSORIES

Current Indicator Light.

Crescendo Indicator Light.

Organist's bench with blocks for height adjustment, *Curved front.*

Back Rest for Bench, *Curved.*

A. G. O. standard Pedal keyboard.

Organ Blower and Motor of ample capacity.

Action current power unit.

Static reservoir on blower.