

M. P. MÖLLER Organ Factory

2|12+2

Pipe Organ No. 9851 Date March 25, 1963 Revised 2/18/64
 For THE FEDERATED CHURCH, WEST LAFAYETTE, INDIANA
 Action Moller's Pitman Electro-Pneu. Console Detached. Electro-Pneu., Level
 Casing No. None Finish As Per Sample Manuals.
 Decorations None Motor 1-1/2 HP Style 3-P-2724
 Width of Key-bed Standard Stop Controls Tablet Type
 No. Manuals TWO Heavy cut English Ivory Keys. Wind Pressure Gt. 3 1/2", Sw. 4", Ped. 3 1/2"
Multiple Contacts with
gang switches.
 To be Completed March 15, 1964 Blower Pipe furnished by Purchaser

PITCH: A-440

SPECIFICATIONS

GENERAL: The organ shall be a distinctive work of the builder, a product of his factory, in no way a stock or assembled instrument.

GREAT ORGAN (Unenclosed) 5+1

- | | | |
|----|----------|--|
| 1. | 8' | Principal.....46.....18-1/2.....12 Zinc S.M....85 Pipes |
| 2. | 8' | Holzgedeckt..1-12 Spec. Bass..#13 Reg. Stopped Flute Wood 73 Pipes |
| 3. | 8' | Gemshorn.....from #9.....61 Notes |
| 4. | 4' | Octave.....from #1.....73 Notes |
| 5. | 2' | Spitzflöte.....(console only) |
| 6. | III Rks. | Mixture....Formula "A"..18-1/2.....S.M...183 Pipes |
| 7. | | Tremolo |

SWELL ORGAN (Enclosed) 6+1

- | | | |
|-----|--------|--|
| 8. | 8' | Rohrflöte.....54.....21-1/2.....12 Zinc S.M....61 Pipes |
| 9. | 8' | Gemshorn.....54-1/2...17-1/2.....12 Zinc S.M....61 Pipes |
| 10. | 8' | Gemshorn Celeste...(console only) |
| 11. | 4' | Nachthorn.....60.....19-1/2.....S.M....61 Pipes |
| 12. | 2' | Prinzipal.....70.....17-1/2.....S.M....61 Pipes |
| 13. | 1-1/3' | Larigot.....82-2/3...17-1/2.....S.M....61 Pipes |
| 14. | 8' | Trompette.....2-1/2"...42-1/2.....S.M....61 Pipes |
| 15. | | Tremolo |

PEDAL ORGAN (Unenclosed) 1

- | | | |
|-----|-----|---|
| 16. | 16' | Bourdon..Wood..Reg. Ped. Bdn...12 pipes 20 from #2.....32 Notes |
| 17. | 16' | Quintaton...42...21 1/2...20-1/2...12 pipes 20 from #8.....32 Notes |
| 18. | 8' | Spitzprinzipal....46-3/4...18-1/2.....12 Zinc S.M....44 Pipes |
| 19. | 8' | Rohrflöte..... from #8.....32 Notes |
| 20. | 4' | Octave.....from #18.....32 Notes |
| 21. | 16' | Double Trumpet...(console only) |
| 22. | 4' | Clarion.....(console only) |

COUPLERS

- 23. Great to Pedal 8'
- 24. Swell 16'
- 25. Swell 4'
- 26. Great 4'
- 27. Swell to Pedal 8'
- 28. Swell to Pedal 4'
- 29. Swell to Great 16'
- 30. Swell to Great 8'
- 31. Swell to Great 4'

ADJUSTABLE COMBINATIONS

- Pistons No. 1-2-3 Affecting Great and Pedal Organs
- Pistons No. 1-2-3 Affecting Swell and Pedal Organs
- Pistons No. 1-2-3 General, Affecting Entire Organ

ACCESSORIES

Swell expression pedal
 Crescendo pedal for entire organ, with indicator light, Tremolo cut-out switch.
 Heavy English Ivory Manual Keys.
 Swell box partitions, swell shade actions with separate reservoir wind supply,
 as required.
 Station cut-out switches when no stops are drawn.
 Circuit breaker organ action protection, 15 amp. maximum per circuit.
 Orgelectra action current rectifier in loft, with wind switch.
 Static blower reservoir.
 Electric motor, steel slow-speed Kinetic blower, as required.
 Great to Pedal Reversible Piston, duplicated to pedal at right.
 Music rack light.

The organ shall be assembled and tested at the factory, delivered, installed
 and finished (tone-regulated) in the church by Moller staff.

MIXTURE FORMULA

Great III Rks. Mixture Formula "A"

15	12	8
19	15	12
22	19	15
1-36	37-48	49-61

Unison	48 scale @ 8' CC	18-1/2	1/4 mouth	S.M.
Quint	49 scale @ 8' CC	18-1/2	1/4 mouth	S.M.

JHH/mb

8/7/63

Salesman: Henry Beard

Revised

2/18/64 JHH/mb