# M. P. MÖLLER Organ Factory

	Before the profession of the p	and the second s
Pine Organ No.	R-887	Date March 13, 1973
For	ST. JOHN'S EPISCOPAL CHURCH,	NORTH ADAMS, MASSACHUSETTS
	Blectro-Pneumatic	
Casing No.	Present case - no change	Finish To customer's sample
Decorations	Present and new display pipes	Motor Present motor and blower
Width of Key-bed.	Standard	Stop Controls Draw Knobs & Tilting Tablet
		Wind Pressure
To be Completed_	December 1, 1973	Blower Pipe furnished by PURCHASER
	CONTRACTOR	OXIG

#### SPECIFICATIONS

#### FOR

REBUILDING, CHANGING TONALLY, AND ADDING TO PRESENT MOLLER ORGAN OPUS 3712 - 1923

CONSOLE Install new three manual, electro-pneumatic, detached, draw knob type console, pedal key and organ bench.

MANUAL CHESTS Recover 1461 manual pipe pouches.

Install 1461 stop action checks and eyelets.

Recover one 61 note and two 73 note primary stations, and

install new outside type magnets.

Recover 21 stop action primaries and install new outside

type magnets.

Recover 16 Bourdon pedal primary #1-#44.

Install 49 shifters and necessary stop action for

Great 8 Harmonic Flute #13-61.

Install new action for the following:

Great III Mixture - 183 pipes Swell III Mixture - 183 pipes

OFFSET CHESTS Recover display pipe action for Great 8 Open Diapason and install new outside type magnets.

Install new action for Great 8 Harmonic Flute #1-12.

SWITCHES Install the following new switches with stop actions:

Great 8 Open Diapason 17 notes 12 notes Great 8 Harmonic Flute 61 notes Great III Mixture Great Station cutout 61 notes Swell 16 Bourdon 44 notes 61 notes Swell III Mixture 73 notes Swell Station cutout Choir Station cutout 73 notes PEDAL ORGAN

Recover the following actions and install new outside type magnets:

16	Open Diapason	#1-32
16	Violone	#1-12
16	Bour don	#1-32

Install the following new actions:

16 Violone #13-44 4 Octave #1-44

Install new 32 note relay with necessary switches.

EXPRESSION

Recover two 10 note expression actions and install new outside type magnets.

Recover 20 shade and bumper pneumatics.

Install 20 new shade jacks and connecting rods.

RESERVOIRS

TREMOLOS

Recover the following reservoirs and install new curtain valves as required:

One 3'-0" x 5'-0" manual Two 2'-6" x 4'-0" manual Three pedal Two expression One console

Install new 3'-0" x 3'-0" blower reservoir.

Install new reservoirs as required for new actions.

Rebuild two present electro-preumatic tremolos sprovide one additional similar reconditioned tremolo-from inventory.

Revoice Choir 8 Clarinet - 73 pipes. PIPES

Repack all present wood pipe stoppers.

Install new slide tuners as required.

Install the following new pipes:

61 pipes (17 on display) 10 Great 8 Open Diapason

Great 8 Harmonic Flute 12 pipes Great 2 Super Octave 61 pipes Great III Mixture 183 pipes Swell 4 Principal 73 pipes

Swell 2-2/3 Nazard 73 pipes

Swell III Mixture 183 pipes

CABLES

Install new plastic covered cables between console and organ. Install new action current wires between console, organ and power unit.

ACTION CURRENT Present DC organ power unit to be used without change.

BLOWER Reuse present Style 2 JZM, 3 HP blower without change.

Install new 14" diameter flexible connections with draw bands.

Install new motor-blower coupling leathers.

DISPLAY PIPES Refinish existing display pipes to sample for new display

pipes.

GENERAL Entire organ (except organ case and blower) to be returned

to the factory of M. P. Moller, Inc. at Hagerstown, Maryland

for rebuilding as specified above.

## SPECIFICATIONS FOR CONSOLE AND ORGAN

MANUAL COMPASS PEDAL COMPASS WIND PRESSURE

PITCH

CC to C4, 61 notes CCC to G, 32 notes

A-440 @ 70°F

## GREAT ORGAN (Enclosed with Choir) 8

*	1	8	Open Diapasonnew pipes; present action
			(#1-17 on display)
	2	8	Harmonic Flutenew pipes and action #1-12
			present 4 Harmonic Flute pipes and
			action #13-7373 pipes
	3	8	Genshorn
*	4	4	Octave
	5	4	Harmonic Flutefrcm #2
	6	2	Super Octave
*	7	III	Mixture
	8		Tremolo (Flutes and String only)
	9		Blank

## (\*) Unenclosed

#### SWELL ORGAN (Enclosed) 14

10	16	Bourdon73 pipes
11	8	Open Diapasonpresent pipes and action73 pipes
12	8	Stopped Diapasonpresent pipes and action73 pipes
13	8	Salicionalpresent pipes and action73 pipes
14	8	Voix Celeste TCpresent pipes and action
15	4	Principalnew pipes; present Violina action73 pipes
16	4	Flute Traversopresent pipes and action73 pipes
17	2-2/3	Nazard new pipes; present Acoline action73 pipes
18	2	Fifteenth73 pipes and action73 pipes
19	III	Mixture
20	8	Trumpetpresent Cornopean pipes and action73 pipes
21	4	Oboe Clarion#1-61 present 8 Oboe pipes #13-73;
	,	new top Octave; present 8 Oboe action. 73 pipes
22		Tremolo

## CHOIR ORGAN (Enclosed) 5

23	8	Violin Diapasonpresent pipes and action
24	8	Melodia
25	8	Dulcianapresent pipes and action
26	4	Flute D'Amourpresent pipes and action73 pipes
27	8	Clarinetpresent pipes and action
28		Tremolo
		** PEDAL CRGAN 4
		GENERAL POINT AND
29	16	Open Diapasonpresent pipes and action32 pipes
30	16	Violone#1-12 present pipes; #13-44 present Great 8
		Gamba pipes; #1-12 present action; #13-44
		new action
31	16	Bourdonpresent pipes and action32 pipes
32	-8	Bass Flute32 notes
33	8	Cello
34	4	Octave44 pipes and action44 pipes
35	2	Super Octavefrom #34
36		Blank
37		Blank

## (\*\*) Pedal organ playable thru new relay and switches.

## COUPLERS

38	Great to Pedal	53 Swell to Choir 16
39	Great to Pedal 4	54 Swell to Choir
40	Swell to Pedal	55 Swell to Choir 4
41	Swell to Pedal 4	56 Great 16
42	Choir to Pedal	57 Great Unison
43	Choir to Pedal 4	58 Great 4
44	Swell to Great 16	59 Swell 16
45	Swell to Great	60 Swell Unison
46	Swell to Great 4	61 Swell 4
47	Choir to Great 16	62 Choir 16
48	Choir to Great	63 Choir Unison
49	Choir to Great 4	64 Choir 4
50	Choir to Swell 16	
51	Choir to Swell	
52	Chair to Swell A	

## ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3-4-5 Pistons No. 1-2-3-4-5 Pistons No. 1-2-3-4 Toe Studs No. 1-2-3-4-5 Pistons No. 1-2-3-4-5

Affecting Great Stops Affecting Swell Stops Affecting Choir Stops Affecting Pedal Stops Generals affecting all stops and couplers. duplicated by toe studs.

General Cancel

## REVERSIBLES

Great to Pedal - manual piston and toe stud Swell to Pedal - manual piston and toe stud Choir to Pedal - manual piston and toe stud Tutti - manual piston and toe stud - indicator light (red jewel)

## PEDAL MOVEMENTS

Balanced Expression Pedal - Swell Organ (10 contacts, regular system) Balanced Expression Pedal - Great-Choir Organ (10 contacts, regular system) Balanced Crescendo Pedal with indicator light (green jewel)

## **ACCESSORIES**

Concave, radiating pedal clavier Organ bench with music shelf Music rack light Pedal light Present motor and blower Present DC organ power unit

RVK/mr 4/12/73