

3489

SPECIFICATION No. 206-GR-06

DATE November 9, 1979

DESIGNED FOR ST. MARY MAGDALEN

MELVINDALE, MICHIGAN

3489

	FEET	PIPES
<u>GRAND ORGUE</u>		
1. Montre (prepared in console only)	8	--
2. Flûte à cheminée " " "	8	--
3. Prestant " " "	4	--
4. Fourniture " " "	IV	--

<u>RECIT</u>		
5. Bourdon	8	56
6. Viole de gambe	8	56
7. Flûte conique	4	56
8. Doublette	2	56
9. Trompette Tremblant	8	56

<u>PEDALE</u>		
10. Soubasse (Extension of #2)	16	12
11. Octavebasse	8	32
12. Flûte à cheminée (from Grand Orgue)	8	--
13. Octave (Extension of #11)	4	12
14. Basson (cylindrical) prepared in console only	16	--

<u>COUPLERS</u>		
Grand Orgue to Pédale	8'	
Récit to Pédale	8'	
Récit to Pédale	4'	
Récit to Grand Orgue	16'	
Récit to Grand Orgue	8'	
Récit to Récit	16'	
Récit to Récit	4'	
Récit Unison Off		

BALANCED PEDALS

Crescendo on all stops and couplers
Récit Expression

vraie copie 21/11/79

ACCESSORIES

- Concave and radiating pedal clavier
- Organist's bench with music shelf
- Wind-on indicator light (pedalboard light)
- Crescendo indicator light
- Light incorporated in music rack

The console shall be all-electric and detached from the organ.

The stops and couplers shall be controlled by tilting tablets placed above the upper keyboard.

The console case, the organist's bench and the pedalboard shall be of oak, finished to match surrounding woodwork. A sample of the wood and finish shall be furnished by the Purchaser at least six (6) months prior to the date of delivery.

Manual natural keys shall be of ebony; manual sharps shall be of rosewood with ivory caps. Pedal sharps shall be of rosewood.

Tilting tablets and combination thumb pistons shall be of rosewood.

The music rack shall be of tempered plate glass, of the hinged type, in the tablet board.

The keyboards shall have a roll-top cover; the start-stop switch for the blower shall be in the console.

There shall be a light incorporated into the ledge of the music rack.

There shall be a light for the pedalboard.

No casework, grilles or special treatment to exposed pipework are included in this specification. These items, if they are to be supplied by the Builder, shall become the subject of separate estimates and purchase agreements when the organ and façade are determined.

There shall be a blower and motor of ample capacity and a rectifier for the low voltage current provided by the Builder. The Purchaser shall furnish the electrical current characteristics at least six (6) months prior to the date of delivery.

CASAVANT FRERES LIMITEE, St. Hyacinthe, Québec, Canada.