

SPECIFICATIONS

FOR A

215

REUTER PIPE ORGAN

~~1961~~ 1961

FOR

XAVIER HOSPITAL CHAPEL

DUBUQUE, IOWA.

TWO MANUAL & PEDAL

THE REUTER ORGAN COMPANY  
LAWRENCE, KANSAS.

January 9, 1959

R. W. Dirksen  
District Representative

225 West Cleveland St.  
Freeport, Illinois.

21122  
U S

Cloud  
1982 Cons w/ Meroy 41  
1984 Windsor Pile Ret. Ectox  
Windsor 2 Dany  
E16 353

## GENERAL SPECIFICATIONS

MANUALS	Compass CC to C4, 61 notes.
PEDALS	Compass CCC to G, 32 notes.
ACTION	Reuter's Electro-pneumatic Pitman action.
REGISTRATION	Controlled by Stop Keys.
PITCH	A-440.
CONSOLE	plain slab design of hard wood finished to match interior woodwork of Chapel. Detached from organ and placed to suit purchaser. The console is to be mounted on a platform with heavy castors so that it may be moved and turned as desired within a given area.
EXPOSED DIVISION	The 8' Bourdon and 4' Principal of the Great division are to be exposed and placed directly in front of the tone opening of the organ chamber. The low twelve pipes of the 16' Bourdon are to be exposed and will be placed at the right side of the organ chamber and against the rear wall of the gallery. The low 16' Octave of the Bourdon will be an extension of the exposed Great 8' Bourdon.
CASEWORK & GRILLE	None except that of console.
ORGAN CHAMBER	The stops of the Swell organ and the stops of the Great which are borrowed from the Swell will be placed in the organ chamber and will be under expression. The present metal Grille will be removed from the tone opening and the opening enlarged so that it will extend to the ceiling of the organ room. The removal of the grille and the enlarging of the opening to be done by the purchaser and at their expense.
ORGAN BLOWER	The present blower will be used and will be placed in the closet under the right side of the gallery.

- |    |     |       |            |         |                              |           |
|----|-----|-------|------------|---------|------------------------------|-----------|
| 1. | ✓ * | 8 ft. | Bourdon    | 53      | metal                        | 61 pipes. |
| 2. | ✓   | 8 ft. | Spitzflöte | (metal) | ( from swell ) <sup>#1</sup> | 61 notes. |
| 3. | ✓   | 8 ft. | Salicional | (metal) | ( from swell ) <sup>#8</sup> | 61 notes. |
| 4. | ✓ * | 4 ft. | Octave     | 59      | metal                        | 61 pipes. |
| 5. | ✓   | 2 ft. | Fifteenth  | (metal) | ( from swell ) <sup>#7</sup> | 61 notes. |

## COUPLERS TO GREAT:

Swell to Great Sub.

Swell to Great Unison

Swell to Great Super.

Great to Great Sub.

Great Unison Off.

Great to Great Super.

( \* ) Stops so marked will be installed in an exposed position in front of organ chamber.

The stops borrowed from the Swell are strictly for registration purposes. They will not be affected by the Great couplers but will play only at the pitch designated.

SWELL ORGAN

4" w

6.	✓✓ 16 ft.	Spitzflote T.C.	(metal) <i>From #7</i>	49 notes.
7.	✓✓ 8 ft.	Spitzflote	metal 49 $\frac{1}{2}$ top $\frac{1}{2}$ m	61 pipes.
8.	✓ 8 ft.	Salicional ( <i>quiet</i> )	metal 52 Dolcan	61 pipes.
9.	✓✓ 8 ft.	Voix Celeste T.C.	metal 52 Dolcan	61 pipes.
10.	✓✓ 4 ft.	Principal	(metal) <i>From #7</i>	12 pipes.
11.	✓✓ 4 ft.	Violin	(metal) <i>From #8</i>	12 pipes.
12.	✓✓ 2-2/3 ft.	Nasard	(metal) <i>From #7</i>	61 notes.
13.	✓✓ 2 ft.	Blockflote	(metal) <i>From #7</i>	12 pipes.
14.		Tremolo		

## COUPLERS TO SWELL:

Swell to Swell Sub.

Swell Unison Off.

Swell to Swell Super.

PEDAL ORGAN

15.	✓ 16 ft.	Bourdon <del>4</del>	wood ( extension #1 )	12 pipes.
16.	✓✓ 16 ft	Gedeckt	wood(Soft wind device)	12 notes.
17.	✓✓ 8 ft.	Spitzflote	metal <i>From #7</i>	32 notes.
18.	✓ 4 ft.	Flute	metal <i>From #7</i>	32 notes.

## COUPLERS TO PEDAL:

Great to Pedal Unison.

Great to Pedal Super.

Swell to Pedal Unison.

Swell to Pedal Super.

## ADJUSTABLE COMBINATIONS

Operated by thumb pistons under the Swell manual.  
Adjustable at keyboard and visibly affecting the Stop Controls.

Three, Generals acting on all stops and couplers.

## PEDAL MOVEMENTS

Expression pedal for enclosed section.

Register Crescendo Pedal.

Great to Pedal Reversible.

## ACCESSORIES

Crescendo Indicator Light.

Wind Indicator Light.

Plexiglass Music Rack with built in Fluorescent Light.

ORGANISTS BENCH WITH MUSIC SHELF

Concave Radiating Pedal Keyboard, A.G.O. Model.

Action current power unit.

Static reservoir at blower.

Present blower to be used. This is a new  $\frac{1}{2}$  H.P. Orgablo.