

SPECIFICATIONS FOR ORGAN

ST. PAUL'S CHURCH
Selma, Alabama

COMPAES OF MANUALS
COMPASS OF PEDAL

61 Notes
32 Notes

Keyaction -
Stopaction -

Mechanical
Electric

PEDAL ORGAN

16'	PRINCIPAL	32 Pipes
16'	Pommer	Great
8'	OCTAVE	32 Pipes
8'	FLUTE	32 Pipes
4'	CHORALBASS	32 Pipes
4R	RAUSCHBASS 2-2/3'	128 Pipes
16'	POSAUNE	32 Pipes
8'	TRUMPET	32 Pipes

GREAT ORGAN

16'	POMMER	61 Pipes
8'	PRINCIPAL	61 Pipes
8'	GEMSHORN	61 Pipes
8'	ROHRGEDACKT	61 Pipes
4'	OCTAVE	61 Pipes
4'	SPITZFLOTE	61 Pipes
2-2/3'	QUINTE	61 Pipes
2'	SUPEROCTAVE	61 Pipes
1-3/5'	TIERCE	61 Pipes
4R	MIXTURE 1-1/3'	244 Pipes
8'	TRUMPET	61 Pipes

SWELL ORGAN

8'	GAMBA	61 Pipes
8'	VOIX CELESTE	56 Pipes
8'	COPULA	61 Pipes
4'	PRINCIPAL	61 Pipes
4'	ROHRPFEIFE	61 Pipes
2'	BLOCKFLOTE	61 Pipes
1-1/3'	LARIGOT	61 Pipes
3R	SCHARF 1/2'	183 Pipes
16'	DULZIAN	61 Pipes
8'	OBOE	61 Pipes
	TREMOLO	

COUPLERS

GREAT TO PEDAL

SWELL TO PEDAL

SWELL TO GREAT

COMBINATIONS By Setterboard

GENERALS 1-2-3-4-5-6-7-8

PEDAL 1-2-3-4-5-6

GREAT 1-2-3-4-5-6

SWELL 1-2-3-4-5-6

ACCESSORIES

Blower

AC/DC Rectifier

Organists Bench with Crank Height Adjustment

Swell Pedal

Full Organ Reversible

Full Organ Indicator Light

Manual Natural Keys - Plumwood

Manual Sharp Keys - Palisander Wood

Stop Tablets - Cherry Wood

Crescendo Pedal

Crescendo Indicator Light

General Cancel

CASEWORK

The casework shall reflect the design submitted by Holtkamp Organ Company September, 1976. The casework shall consist of the choir platform, the console and bench, and the case surrounding the organ. The console, bench and organ case shall be in plain sliced red oak finished to an approved sample.

The front pipes of the 16' PRINCIPAL shall be in pure zinc finished to an approved sample. The remaining front pipes shall be in spotted metal in a natural finish.