

SPECIFICATION No. 220-GR-25

DATE October 7, 1988

DESIGNED FOR ALL SAINTS EPISCOPAL CHURCH

HOMEWOOD (BIRMINGHAM), ALABAMA

	GRAND ORGUE	FEET	PIPES
* 1.	Bourdon (Wood, extension of No. 3)	16	12
	2. Montre	8	61
* 3.	Bourdon	8	61
	4. Prestant	4	61
* 5.	Flûte à fuseau	4	61
* 6.	Nazard	2-2/3	61
* 7.	Quarte de nazard	2	61
* 8.	Tierce	1-3/5	61
	9. Fourniture	IV	244
10.	Trompette	8	61
* <i>mp</i>	<i>Chimes (console prep.)</i>		
	Stops marked thus under expression.		

RECIT

11.	Flûte à cheminée	8	61
12.	Viole de gambe	8	61
13.	Voix céleste (GG)	8	54
14.	Principal	4	61
15.	Doublette	2	61
16.	Cymbale	III	183
17.	Hautbois	8	61
	Tremblant		

PEDALE

18.	Soubasse	16	32
19.	Bourdon (Grand Orgue)	16	--
20.	Octavebasse	8	32
21.	Bourdon (Grand Orgue)	8	--
22.	Octave	4	32
23.	Bombarde (Full-length)	16	32
24.	Trompette (Grand Orgue)	8	--

ANALYSIS

	<u>Stops</u>	<u>Ranks</u>	<u>Pipes</u>
Grand Orgue	9	12	744
Récit	7	9	542
Pédale	4	4	128
Totals:	20	25	1414

*Maie copie*  
*(12/10/88)*

### INTER-MANUAL COUPLERS

Grand Orgue /	Pédale	8
Récit /	Pédale	8
Récit /	Pédale	4
Récit /	Grand Orgue	16
Récit /	Grand Orgue	8

### ADJUSTABLE COMBINATIONS (Hold-set)

Grand Orgue	1	2	3	4				Thumb
Récit	1	2	3	4				Thumb
Pédale	1	2	3	4				Toe
General	1	2	3	4	5	6		Thumb & Toe
Cancel								Thumb

### REVERSIBLE PISTONS

Grand Orgue /	Pédale	Thumb & Toe <i>apd</i>
Full Organ		Toe

### BALANCED PEDALS

Crescendo on all stops and couplers  
Grand Orgue Expression  
Récit Expression

### ACCESSORIES

Concave and radiating pedal clavier  
Organist's bench with music shelf and backrest  
Adjustable bench blocks  
Wind-on indicator light  
Crescendo indicator light  
Full Organ indicator light

The console shall be all-electric and detached from the organ.

Stops and couplers shall be controlled by rosewood tilting tablets placed above the upper keyboard. Combination thumb pistons shall be of rosewood.

Console case, organist's bench and pedalboard shall be of oak, finished to match surrounding woodwork.

Manual natural keys shall be of ebony; manual sharps shall be of rosewood with ivory caps. Pedal sharps shall be of rosewood.

The keyboards shall have a roll-top cover; the start-stop switch for the blower shall be in the console.

The hinged-type music rack shall be of tempered plate glass, in the tablet board, with a light incorporated in its ledge.

There shall be a light for the pedalboard.

No casework, grilles or special treatment to exposed pipework are included in this specification. These items, if they are to be supplied by the Builder, shall become the subject of separate estimates and purchase agreements when the organ and façade are determined.

There shall be a blower and motor of ample capacity in a sound absorbing enclosure, and a rectifier for the low voltage current, provided by the Builder.

---

CASAVANT FRERES LIMITEE, St. Hyacinthe, Quebec, Canada.

Manual natural keys shall be of ebony; manual sharps shall be of rosewood with ivory caps. Pedal sharps shall be of rosewood.

The keyboards shall have a roll-top cover; the start-stop switch for the blower shall be in the console.

The hinged-type music rack shall be of tempered plate glass, in the tablet board, with a light incorporated in its ledge.

There shall be a light for the pedalboard.

No casework, grilles or special treatment to exposed pipework are included in this specification. These items, if they are to be supplied by the Builder, shall become the subject of separate estimates and purchase agreements when the organ and façade are determined.

There shall be a blower and motor of ample capacity in a sound absorbing enclosure, and a rectifier for the low voltage current, provided by the Builder.

---

CASAVANT FRERES LIMITEE, St. Hyacinthe, Quebec, Canada.